

tightening torque/thread 1.0 Nm/M 3 Inspection Test Pattern Size A 4

Type Cat.-No. Qty.p.pck.  
**SRD 4-800** 41025.2 beige 80


### Ratings:

	UL	CSA	DIN-VDE	IEC
Rated Voltage	600 V	600 V	611 750 V	800 V
Rated Current	30 A AWG 12	34 A	34 A	32 A

### Max Rated Cross Section

Single Wire (solid)	0.2-4 mm <sup>2</sup>
Stranded Wire (flexible)	0.2-4 mm <sup>2</sup>
Wire Size	AWG 22-12

Dimensions	TS 32	TS 35
LxBxH (mm)	61x7.5x65	61x7.5x60
Stripped Length	9 mm	



tightening torque/thread 0.7 Nm/M 2.5 Inspection Test Pattern Size A 3

Type Cat.-No. Qty.p.pck.  
**SR 2.5** 41296.2 beige 100  
**SR 2.5** 41296.5 blue 100

Additional colors available. See page 114.

### Ratings:

	UL	CSA	DIN-VDE	IEC
Rated Voltage	600 V	600 V	611 750 V	800 V
Rated Current	20 A AWG 14	26 A	26 A	24 A

### Max Rated Cross Section

Single Wire (solid)	0.2-4 mm <sup>2</sup>
Stranded Wire (flexible)	0.2-2.5 mm <sup>2</sup>
Wire Size	AWG 22-14

Dimensions	TS 32	TS 35
LxBxH (mm)	48x5x52	48x5x47
Stripped Length	7 mm	

Type:	Cat.-No.	Qty.p.pck.	Terminal accessories	Type:	Cat.-No.	Qty.p.pck.
AP 4/800 V	2159.2 beige	20	End plate	AP 2.5-10	2001.2 beige 2001.5 blue	50
			Isolation partition	TW 2.5-10	2002.2 beige 2002.5 blue	50
			Separator	TRS 3	2566.2 beige	100
ES 32/35 Combi	1424.2 beige	50	End bracket	ES 32/35 Combi	1424.2 beige	50
ES 32/K/ST	2827.0				ES 32/K/ST	
ES 35/2/K	2826.2 beige	50	End bracket	ES 35/2/K	2826.2 beige	50
ES 35/K/ST	2828.0				ES 35/K/ST	
STB 8.5/2.3	2075.0	50	Test socket	STB 8.5/2.3	2075.0	50
PS 2.3	2007.0	20	Test plug	PS 2.3	2007.0	20
			Switchable link			
			Connection sleeve			
			Screw			
			Warning tag (German)	AD 4	2712.0	50
			Warning tag (English)	AD 4 E	2713.0	50
			Plastic screw for warning tag	BSK M 2.5x22	2080.0	100
			Cross-connection	Q2	2567.0	50
			Cross-connection	Q3	2568.0	50
			Cross-connection	Q4	2569.0	20
			Cross-connection	Q10	2570.0	10