



Scan the QR code and visit the product page



Code	<b>TK.LB.W0410.AEC</b>	Safety level	Warning
Dimensions (H x L)	69 mm x 160 mm (2,7" x 6,3")	Version	Standard
Material	PVC base with adhesive liner and protective layer	Temperatures <sup>(1)</sup>	-40°C/+95°C
Applications	Machinery and control panels. Indoor and outdoor locations		
Languages <sup>(2)</sup>	Inglese		
Message <sup>(3)</sup>	EN: Crush hazard. Exposed gears or moving parts can cause severe injury. Lock out power before removing guard or doors. IT: Pericolo di schiacciamento. Gli ingranaggi o le parti esposte in movimento possono causare lesioni gravi. Mettere in sicurezza prima di rimuovere la protezione o le porte.		
Certifications	c(UL)us Recognized - File#MH60136 (PDGQ2, PGDQ8)		
Standards of use	ANSI Z535, OSHA Art. 1910.145, NFPA 70 (NEC), NFPA 79, UL 508A, CSA C22.1 (CECode), CSA C22.2 No.286		
Standards Construction	ANSI Z535, UL 969, CSA C22.2 No.0.15, ISO 3864, RoHS		
Standard packaging	12 pz/pcs		

(1) For indoor and outdoor exposure with high humidity or with occasional exposure to water. The minimum application temperature is +0°C. UL certification is for maximum working temperatures of +60°C.

(2) Other languages may have different sizes and available upon request.

(3) The message and the image are shown in English language only.