



NOTES:  
1. CAPTURED CENTER CONTACT

DESIGNED FOR USE WITH RG174, RG316	
CABLE ENTRY DIAMETER MINIMUM	020
SLEEVE	067
CONTACT	023

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
020	REVISED	5/30/97	Janczar <i>PW</i>

HOUSING CLAMP NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	GOLD PLATE PER MIL-G-45204
COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER GO-P-35
DIELECTRIC	PTFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
RETAINING RING	BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H	GOLD PLATE PER MIL-G-45204
RETAINING RING	BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H	N/A
SLEEVE	BRASS PER ASTM-B-16, HALF HARD	GOLD PLATE PER MIL-G-45204
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A
SHRINK TUBING	HEAT SHRINKABLE POLYOLEFIN COMPOUND MIL-I-23053/4	N/A
FERRULE	COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM	GOLD PLATE PER MIL-G-45204

COMPONENT	MATERIAL	FINISH
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN BY L ROSS DATE 3-15-89 CHECKED BY K.C. MAHER 3/16/89 APP'D BY LB 4/5/89	<b>MACOM</b> an AMP company M/A-COM, Inc. Waltham, MA 02254
GEN. TOL. ±.005	ANGLES ± 1°	TITLE OSSM STRAIGHT CABLE PLUG- CRIMP ATTACHMENT
USE ASSY PROCEDURE	NO. AP. 10-055	SIZE B
NO. AP. 10-055	SCALE 4:1	CODE IDENT NO. 26805
		1031-5031-92
		REV 020
		SHEET 1 OF 1

ELECTRICAL	MECHANICAL	ENVIRONMENTAL
Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-378A, Fig 319.1	Temperature Rating -65°C to +105°C
Frequency Range (GHz) DC to 12.4	Recommended Mating Torque 5 in-lbs	Vibration MIL-STD-202, Method 204, Condition D.
Volt Rating (VRMS MAX) @ Sea Level 250	Mating Characteristics Insertion (MAX Lbs) N/A Withdrawal (MIN Oz) N/A	Shock MIL-STD-202, Method 213, Condition I.
VSWR 1.07 ±0.15 (1GHz)	Force to Engage and Disengage (In-Lbs MAX) 2.0	Thermal Shock MIL-STD-202, Method 107, Condition B, Except High Temp +105°C
Insertion Loss (dB MAX) .04 √(MHz)	Center Contact Captivation Axial (Lbs) 4.0 MIN Radial (In-Oz) N/A	Moisture Resistance MIL-STD-202, Method 106
RF Leakage (dB MIN) -60 @ 2-3 GHz	Cable Retention Axial Force (Lbs MIN) 20.0	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray
Corona, 70,000 Ft (VRMS MIN) 150	Torque (In-Oz) N/A	
Dielectric Withstanding Voltage (VRMS MIN @ Sea Level) 750	Weight (Grams) TBD	
Contact Resistance (Milliohms MAX) Center Contact 20 Outer Contact 2.0		
Cable to Housing 0.5		
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 500		
I.R. (Megohms MIN) 5,000		

.XXX = In  
XX.X = mm (REF)

CUSTOMER

1045486

SHEET 1 OF 1  
REV 0