


THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION

© COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
AF	50	P	LTR	DESCRIPTION	DATE	DWN	APVD
		T		REVISED PER ECR-13-004343	30JUL13	KH	KR

- 1 MATES WITH .032±.001x.250 TAB
- 2 WIRE STRIP LENGTH .281
- 3 INSULATION SIZE .160 MAX DIA
- 4 CONTINUOUS STRIP ON REELS
- △5 DIMENSION DOES NOT INCLUDE TRIM BURR
- △6 .015 MAX CARRIER TRIM BURR PER SIDE IS ALLOWABLE IN THE SHADED AREA



BULK	HOUSING: NYLON, COLOR-BLUE TRANSLUCENT	5-350819-2
STANDARD	RECEPTACLE: BRASS TIN	3-350819-2
PACKAGING	MATERIAL & FINISH	PART NO
THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN P FORTNEY 10/6/88
DIMENSIONS: INCHES		CHK JR RUTH 10/6/88
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD K RANDOLPH 10/6/88
0 PLC ± -		NAME STE TE Connectivity RECEPTACLE ASSY, ULTRA-FAST, .250 SERIES, 16-14 AWG
1 PLC ± -		
2 PLC ± -		
3 PLC ± .015		
4 PLC ± -		PRODUCT SPEC 108-2043
ANGLES ± -		APPLICATION SPEC 114-2123
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT -
		SIZE A3
		CAGE CODE 00779
		DRAWING NO C-350819
		RESTRICTED TO -
CUSTOMER DRAWING		SCALE 4:1
		SHEET 1 OF 1
		REV T