

CL1000 Series

Anti-Static Cellulose Tape

Description

Transforming Technologies ESD safe clear cellulose tape is hand tear-able and biodegradable. It is coated with a Solvent Based Natural Rubber Adhesive which provided excellent tack and holding power. Used for general purpose mending, binding packaging and carton sealing. Meets Specification No. CID-AA-113B, Type 1, Class A.

Meets or exceeds requirements of ANSI ESD-S20.20.



Product Specifications

| | |
|-------------------------|--|
| Backing: | 35 micron Pure Cellulose |
| Thickness: | 2.0 mils (.050mm) |
| Adhesive: | Solvent Based Natural Rubber |
| Adhesion: | 34 oz/inch |
| Ball Tack: | 20# |
| Holding Strength: | 1/32" per 2 hours |
| SST Plate: | 1/2" x 1"; 1 kg. load |
| Tensile Strength: | 24lbs/inch |
| Elongation: | 22% at break |
| Temperature Resistance: | 32°F to 150°F (0°C to 66°C) |
| Shelf Life: | 1-year in conditions of 70°F, 70% Humidity, No direct sunlight |

Product Number

| <u>Item Number</u> | <u>Description</u> |
|--------------------|------------------------|
| CL1200 | 1/2" (12mm) x 72 yards |
| CL1801 | 3/4" (18mm) x 72 yards |
| CL2402 | 1" (24mm) x 72 yards |
| CL4803 | 2" (48mm) x 72 yards |

This document is prepared for our customers as a service, and is to the best of our knowledge true and accurate. However, it is understood and agreed by the users of this document that we will accept no liability for the conclusions reached. Users of this document may therefore wish to perform additional