

[Home](#) > [Products](#) > > [952911](#) > [952911BGLF](#)
[Add to myIDT \[?\]](#)

You may also like...


## 952911BGLF

**Category:**
**Generic Part:** 952911

**Market Group:** PC CLOCK

**Description:** PC MAIN CLOCK

ICS952911 is a 48 pin clock chip for VIA PT890 style chipsets. When used with a fanout DDR buffer, such as the 93788, it provides all the necessary clock signals for such a system. Output Features: â€¢ 2 - 0.7V current-mode differential CPU pairs â€¢ 10 - PCI, 3 free running, 33MHz â€¢ 3 - REF, 14.318MHz â€¢ 3 - 3V66, 66.66MHz â€¢ 1 - 48MHz â€¢ 1 - 24/48MHz â€¢ 2 - 25MHz @ 2.5V



### Parameters

|                         |                  |
|-------------------------|------------------|
| Package                 | TSSOP 48 (PAG48) |
| Speed                   | NA               |
| Temperature             | C                |
| Voltage                 | 3.3 V            |
| Status                  | Active           |
| Sample                  | Yes              |
| Minimum Order Quantity  | 114              |
| Factory Order Increment | 38               |

### Distributor Inventory

No Pricing information is available from our Distributors at this time.

### Documents

| Type | Title                  | Size  | Revision Date |
|------|------------------------|-------|---------------|
| Misc | PC Clocks Contact Info | 61 KB | 05/29/2007    |

### Package

|                                  |                          |
|----------------------------------|--------------------------|
| Description                      | TSSOP 6.10 MM            |
| Class                            | PLASTIC                  |
| Moisture Sensitivity Level (MSL) | 1                        |
| Category                         | Green                    |
| Moisture Exposure Floor Life     | Unlimited @ <30°C/85% RH |
| Peak Reflow Temperature          | 260°C                    |
| Rebake Conditions                | NA                       |
| Length                           | 12.5                     |
| Mark                             | G                        |
| Width                            | 6.1                      |
| Pitch                            | 0.5                      |
| Thickness                        | 1.0                      |
| Status                           | Active                   |