## Customer Information Sheet

DRAWING No.: PIII3XX3 SHEET 2 OF 2 IF IN DOUBT - ASK NOT TO SCALE THIRD ANGLE PROJECTION ALL DIMENSIONS IN mm

SPECIFICATIONS:

MATERIAL:

PLUNGER = PIII3CA3, PIII3CV3 = BRASS PILI3SS3 = HIGH CARBON STEEL

BARRFI = BRASS

SPRING = SPRING STEEL

FINISH: PLUNGER:

PIII3CA3, PIII3CV3 = 0.25µ MIN GOLD

OVER 2.0 MIN NICKEL

PIII3SS3 = 2.0µ MIN NICKEL OVER

BARREL = 0.25µ MIN GOLD OVER 0.5µ COPPER

SPRING = GOLD PLATED

ELECTRICAL:

CURRENT RATING = 2A MAX

CONTACT RESISTANCE = 50mQ MAX

MECHANICAL:

DURABILITY = 100,000 CYCLES

FULL TRAVEL = 3.18mm


SPRING FORCE:

FULL TRAVEL =  $0.75N \pm 0.25N (76.5g \pm 33\%)$ 

2.20mm TRAVEL = 0.54N  $\pm$ 0.11N (55 $\alpha$   $\pm$ 20%)


ENVIRONMENTAL:

TEMPERATURE RANGE = -40°C TO +180°C



## NOTES:

- I. RECOMMENDED CLEARANCE HOLE SIZE =  $\emptyset 2.20\pm0.05$ mm. RECOMMENDED INTERFERENCE HOLE SIZE = \Omega 2.00mm.
- 2. SUITABLE FOR A MINIMUM DISTANCE BETWEEN CENTRES OF 3.00mm.
- 3. THIS PART IS SIMILAR TO PILI3XX2 APART FROM POWER RATING THAT WAS 5A MAX AND MATERIAL/





www.harwin.com technical@harwin.com

INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING. TENDERING OR FOR ANY OTHER PURPOSE WITHOUT

THEIR WRITTEN PERMISSION

 $X. = \pm 1$ mm  $X.X = \pm 0.50 mm$  $X.XX = \pm 0.10$ mm

 $X.XXX = \pm 0.01$ mm ANGLES = ±5° UNLESS STATED

SEE ABOVE

FINISH: SEE ABOVE

mm<sup>2</sup>

S/AREA:

ONE-PIECE SPRING PROBE DRAWING NUMBER:

PIII3XX3

SHT <sup>2</sup> 0F<sub>2</sub>