1393738-2 ACTIVE

AMPLIMITE

TE Internal #: 1393738-2

Shielded, Two-Piece RFI/EMI Shield, Thermoplastic, Straight, Shell

Size 2, 15 Position

View on TE.com >



Connectors > Connector Accessories > Connector Backshells

Connector Backshell Product Style: Shielded

Connector Backshell Product Type: Two-Piece RFI/EMI Shield

Primary Product Material: Thermoplastic

Body Orientation: Straight

Compatible With Connector Shell Size: 2

Features

Product Type Features

Connector Backshell Product Type Two Piece RFI/EMI Shield Connector Backshell Product Type Town Piece RFI/EMI Shield Configuration Features Number of Positions 15 Body Features Primary Product Color Gray Primary Product Material Thermoplastic Cable Exit Angle 37.5° Primary Product Plating Material Nickel over Copper Mechanical Attachment Thread Size 14702 Housing Features Body Orientation Straight Compatible With Connector Shape D-Shaped Dimensions Compatible Insulation Diameter Range 5 – 9 mm[.197 – .355 in] Operation/Application Compatible With Connector Shell Size 2 Packaging Features	Troduct Type reatures		
Configuration Features Number of Positions Body Features Primary Product Color Primary Product Material Cable Exit Angle Primary Product Plating Material Mechanical Attachment Thread Size Housing Features Body Orientation Compatible With Connector Shape Dimensions Compatible Insulation Diameter Range Compatible With Connector Shell Size 2	Connector Backshell Product Style	Shielded	
Number of Positions Body Features Primary Product Color Gray Primary Product Material Thermoplastic Cable Exit Angle 37.5° Primary Product Plating Material Nickel over Copper Mechanical Attachment Thread Size 14702 Housing Features Body Orientation Straight Compatible With Connector Shape D-Shaped Dimensions Compatible Insulation Diameter Range 5 – 9 mm[.197 – .355 in] Operation/Application Compatible With Connector Shell Size 2	Connector Backshell Product Type	Two-Piece RFI/EMI Shield	
Body Features Primary Product Color Gray Primary Product Material Thermoplastic Cable Exit Angle 37.5° Primary Product Plating Material Nickel over Copper Mechanical Attachment Thread Size 14702 Housing Features Body Orientation Straight Compatible With Connector Shape D-Shaped Dimensions Compatible Insulation Diameter Range 5 – 9 mm[.197 – .355 in] Operation/Application Compatible With Connector Shell Size 2	Configuration Features		
Primary Product Color Primary Product Material Cable Exit Angle Primary Product Plating Material Mickel over Copper Mechanical Attachment Thread Size Housing Features Body Orientation Compatible With Connector Shape Compatible Insulation Diameter Range Compatible With Connector Shell Size Compatible With Connector Shell Size 2	Number of Positions	15	
Primary Product Material Thermoplastic Cable Exit Angle 37.5° Primary Product Plating Material Nickel over Copper Mechanical Attachment Thread Size 14702 Housing Features Body Orientation Straight Compatible With Connector Shape D-Shaped Dimensions Compatible Insulation Diameter Range 5 – 9 mm[.197 – .355 in] Operation/Application Compatible With Connector Shell Size 2	Body Features		
Cable Exit Angle Primary Product Plating Material Nickel over Copper Mechanical Attachment Thread Size 14702 Housing Features Body Orientation Compatible With Connector Shape Dimensions Compatible Insulation Diameter Range Compatible With Connector Shell Size 2	Primary Product Color	Gray	
Primary Product Plating Material Nickel over Copper Mechanical Attachment Thread Size 14702 Housing Features Body Orientation Straight Compatible With Connector Shape D-Shaped Dimensions Compatible Insulation Diameter Range 5 – 9 mm[.197 – .355 in] Operation/Application Compatible With Connector Shell Size 2	Primary Product Material	Thermoplastic	
Mechanical Attachment Thread Size 14702 Housing Features Body Orientation Straight Compatible With Connector Shape D-Shaped Dimensions Compatible Insulation Diameter Range 5 – 9 mm[.197 – .355 in] Operation/Application Compatible With Connector Shell Size 2	Cable Exit Angle	37.5°	
Thread Size Housing Features Body Orientation Compatible With Connector Shape Dimensions Compatible Insulation Diameter Range Operation/Application Compatible With Connector Shell Size 2	Primary Product Plating Material	Nickel over Copper	
Housing Features Body Orientation Straight Compatible With Connector Shape D-Shaped Dimensions Compatible Insulation Diameter Range 5 – 9 mm[.197 – .355 in] Operation/Application Compatible With Connector Shell Size 2	Mechanical Attachment		
Body Orientation Compatible With Connector Shape Dimensions Compatible Insulation Diameter Range 5 – 9 mm[.197 – .355 in] Operation/Application Compatible With Connector Shell Size 2	Thread Size	14702	
Compatible With Connector Shape Dimensions Compatible Insulation Diameter Range 5 – 9 mm[.197 – .355 in] Operation/Application Compatible With Connector Shell Size 2	Housing Features		
Dimensions Compatible Insulation Diameter Range 5 – 9 mm[.197 – .355 in] Operation/Application Compatible With Connector Shell Size 2	Body Orientation	Straight	
Compatible Insulation Diameter Range 5 – 9 mm[.197 – .355 in] Operation/Application Compatible With Connector Shell Size 2	Compatible With Connector Shape	D-Shaped	
Operation/Application Compatible With Connector Shell Size 2	Dimensions		
Compatible With Connector Shell Size 2	Compatible Insulation Diameter Range	5 – 9 mm[.197 – .355 in]	
	Operation/Application		
Packaging Features	Compatible With Connector Shell Size	2	
	Packaging Features		

25

Packaging Quantity



5 9	Packaging Method	Box & Tray, Tray
-----	------------------	------------------

Other

Connector Accessory Comment	Knurled screws, cable bushing (grommet)
	and contact tube must be ordered
	separately.

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant	
EU ELV Directive 2000/53/EC	Compliant	
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold	
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) SVHC > Threshold: Perfluorobutane sulfonic acid (PFBS) and its salts (.16% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.	
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free	
Solder Process Capability	Not applicable for solder process capability	

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # CAT-035-DCPPS201 D-Sub Crimp: Plug, Signal, 9 Posn, Pin Size 20, Shell Size 1	TE Part # CAT-AM7-248H3 IDC D-Sub: Plug Assembly, Wire to Wire, Signal, 2.77 mm	TE Part # CAT-AM7-248H8 IDC D-Sub: Receptacle Assembly, Wire to Wire, Signal, 2.74 mm	TE Part # CAT-038-DCRSS221 D-Sub Crimp Recpt Signal 15 Posn, Socket Size 22, Shell Size 1
TE Part # CAT-035-DCRSS201 D-Sub Crimp Recpt Signal 9 Posn, Socket Size 20, Shell Size 1	TE Part # CAT-038-DCPPS221 D-Sub Crimp: Plug, Signal, 50 Posn, Pin Size 22, Shell Size 1	TE Part # 216164-1 15P.HDP22 REC.ASSY.	TE Part # 207752-3 9 CONTACT HSG
TE Part # 6-1393738-0 V42254A6004G115=SUB D GEHAEUSE	TE Part # 1658993-1 OVERMOLD,PLUG ASSY,HDP-22,15 POSN,W/CLIN	TE Part # 167292-2 09P.HDP20 PLUG ASSY	TE Part # 1888305-1 CRIMP SNAP RCPT ASSY,SIZE 1
TE Part # 1888306-1 15 HD22 CRIMP SNAP PLUG	TE Part # 1888308-1 CRIMP SNAP PLUG ASSY,SIZE 1	TE Part # 745202-1 09 HDE AP PLUG HSG	
Customers Also B	ought		
TE Part #5-1879075-6 THS25 22K 5%	TE Part #2-1393561-9 V42254A 262V 19=SUB D SCHRAUBE	TE Part #K1136317 Relay 30-313-12-EC-10-902	TE Part #9-216444-9 SUBASSY FOR 4/4 PCB MOD.JACK B



TE Part #1-111492-5 010 UNIV I/O 30DP NO EARS LTCH

TE Part #2-1393561-8 V42254A 262V 18=SUB D SCHRAUBE

TE Part #3-1825058-1 ADE04SATR04, DIP SW, NO CAP TE Part #5-1393561-5 V42254A6208L 1=SUB D KABELTUE

TE Part #1977208-3 ADF04SATR04900=4POS DIP

TE Part #1977208-4 ADF12SATR04900=12POS DIP

Documents

Product Drawings

V42254A6000G115=SUB D GEHAEUSE

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1393738-2_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1393738-2_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1393738-2_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Environmental Compliance

TE Material Declaration

English

Instruction Sheets

mounting guidline for d-Sub housings

English

Instruction Sheet (U.S.)

English

