



- \triangle HOUSING AND LATCHES: PCT, UL94 V-0 RATED, COLOR RED. POSTS: BRASS.
- \triangle POSTS: GOLD FLASH OVER PALLADIUM-NICKEL PLATE, 0.76 μm [.000030] MIN TOTAL ON THE LOCALIZED PLATE AREA, 2.54 μm [.000100] MIN TIN PLATE ON THE SOLDER-TAIL, 1.27 μm [.000050] MIN NICKEL UNDERPLATE ON THE ENTIRE POST. -OR- 0.76 μm [.000030] MIN GOLD PLATE ON THE LOCALIZED PLATE AREA, 2.54 μm [.000100] MIN TIN PLATE ON THE SOLDER-TAIL, 1.27 μm [.000050] MIN NICKEL UNDERPLATE ON THE ENTIRE POST.
- \triangle DISTANCE REQUIRED BY LATCHES IN OPEN POSITION.
- \triangle RECOMMENDED PRINTED CIRCUIT BOARD THICKNESS 1.57 [.062].
- \triangle RECOMMENDED PAD THICKNESS 0.25 [.010].
- \triangle DATUMS -M- & -N- TO BE ESTABLISHED BY CUSTOMER.

	60.98 [2.400]	68.58 [2.700]	72.64 [2.860]	78.74 [3.100]	82.80 [3.260]	50	1-5111922-0
	30.48 [1.200]	38.10 [1.500]	42.16 [1.660]	48.26 [1.900]	53.32 [2.060]	26	5111922-6
OBSOLETE	48.26 [1.900]	55.88 [2.200]	59.94 [2.360]	66.04 [2.600]	70.10 [2.760]	40	5111922-9
OBSOLETE	17.78 [.700]	25.40 [1.000]	29.46 [1.160]	35.56 [1.400]	39.62 [1.560]	16	5111922-3
OBSOLETE	10.16 [.400]	17.78 [.700]	21.84 [.860]	27.94 [1.100]	32.00 [1.260]	10	5111922-1
	E	D	C	B	A	NUMBER OF POSITIONS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-2009.

DIN 91-12-05
G. ATTADIA - DOCKS
S. BOLASH
M. WALMSLEY
01-12-05

APVD: M. WALMSLEY
NAME: HEADER ASSEMBLY, HIGH-TEMP, UNIVERSAL HEADER, AMP-LATCH
PRODUCT SPEC: 108-40018
APPLICATION SPEC: -

SIZE: A1
CAGE CODE: 00779
DRAWING NO: 5111922
RESTRICTED TO: -

WEIGHT: -
CUSTOMER DRAWING: -
SCALE: 4:1
SHEET: 1 OF 1
REV: E