



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE2300 Silicon NPN Transistor High Voltage, Horizontal Output TO3 Type Package

Description:

The NTE2300 is a silicon NPN transistor in a TO3P type package designed for use in large screen color TV deflection circuits.

Features:

- High Breakdown Voltage and High Reliability
- High Switching Speed

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Collector-Base Voltage, V_{CBO}	1500V
Collector-Emitter Voltage, V_{CEO}	800V
Emitter-Base Voltage, V_{EBO}	7V
Collector Current, I_C	
Continuous	5A
Peak	16A
Collector Dissipation ($T_C = +25^\circ\text{C}$), P_D	120W
Operating Junction Temperature, T_J	+150°C
Storage Temperature Range, T_{stg}	-55° to +150°C

Electrical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector Cutoff Current	I_{CBO}	$V_{CB} = 800V, I_E = 0$	-	-	10	μA
Emitter Cutoff Current	I_{EBO}	$V_{EB} = 5V, I_C = 0$	-	-	1	mA
DC Current Gain	h_{FE}	$V_{CE} = 5V, I_C = 1A$	5	-	-	
Current-Gain Bandwidth Product	f_T	$V_{CE} = 10V, I_C = 1A$	-	3	-	MHz
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 4A, I_B = 0.8A$	-	-	5.0	V
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = 4A, I_B = 0.8A$	-	-	1.5	V
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = 5mA, I_E = 0$	1500	-	-	V
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = 100mA, R_{BE} = \infty$	800	-	-	V
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = 200mA, I_C = 0$	7	-	-	V
Fall Time	t_f	$I_C = 4A, I_{B1} = 0.8A, I_{B2} = -1.6A$	-	-	0.4	μs

