


PART NO. SEE CHART SDA-90573
 DWG. NO.

NOTES:

- MATERIAL:**
HOUSING: POLYESTER, G.F. (UL 94V-0), COLOUR - BLACK.
TERMINAL: PHOSPHOR BRONZE.
- TERMINAL PLATING:**
90573-***1: CONTACT AREA: GOLD FLASH (0.1um)/4uin MIN.
I.D. AREA: TIN-LEAD (1um)/39uin MIN. OVER NICKEL (1um)/39uin MIN. PLATING I.D. MARK: YELLOW.
90573-***2: CONTACT AREA: GOLD (0.76um)/30uin MIN I.D. AREA: TIN-LEAD (1um)/39uin MIN. OVER NICKEL (1um)/39uin MIN. PLATING I.D. MARK: BROWN.
90573-***3: CONTACT AREA: GOLD (0.25um)/10uin MIN I.D. AREA: TIN-LEAD (1um)/39uin MIN. OVER NICKEL (1um)/39uin MIN. PLATING I.D. MARK: BLUE.
- FOR USE WITH No. 26 & 28 AWG STRANDED WIRE (7 CONDUCTORS) AND No. 28 SOLID WIRE 1.14/(.045) DIA. MAX. INSULATION RIBBON CABLE WITH 1.27/(.050) CENTERS.
- MATING STRAIN RELIEF: MOLEX No. 90170.
- DIMENSION "E" IS TOTAL HEIGHT AFTER ASSEMBLED WITH CABLE.
E = (10.2)/.402 REF. WITHOUT STRAIN RELIEF.
E = (15.2)/.598 MAX. WITH STRAIN RELIEF No. 90170, AND (14.5)/.571 REF. WHEN COMPRESSED.
- PRODUCT SPECIFICATION NUMBER : ES 99020-0014.

64	90573-064*	(78.74) 3.100	(82.54) 3.250	(82.71) 3.256	(85.91) 3.382
60	90573-060*	(73.66) 2.900	(77.46) 3.050	(77.63) 3.056	(80.83) 3.182
50	90573-050*	(60.96) 2.400	(64.76) 2.55	(64.93) 2.556	(68.13) 2.682
40	90573-040*	(48.26) 1.900	(52.06) 2.050	(52.23) 2.056	(55.43) 2.182
34	90573-034*	(40.64) 1.600	(44.44) 1.750	(44.61) 1.756	(47.81) 1.882
30	90573-030*	(35.56) 1.400	(39.36) 1.550	(39.53) 1.556	(42.73) 1.682
26	90573-026*	(30.48) 1.200	(34.28) 1.350	(34.45) 1.356	(37.65) 1.482
20	90573-020*	(22.86) .900	(26.66) 1.050	(26.83) 1.056	(30.03) 1.182
16	90573-016*	(17.78) .700	(21.58) .850	(21.75) .856	(24.95) .982
14	90573-014*	(15.24) .600	(19.04) .750	(19.21) .756	(22.41) .882
10	90573-010*	(10.16) .400	(13.96) .550	(14.13) .556	(17.33) .682
NO. OF CKT.	ENG. NO.	A	B	C	D REF.



FOR PREVIOUS DRAWING ISSUES SEE MRI.	OLIVETTI APPROVAL ECN E30020 26 AUGUST 1992 SM	DIMENSIONS SHOWN (METRIC) INCH UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ± 1/2°	DRWG BY PR	CAD/CAM FILENAME SA90573X1 DCN	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. & SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION
	LTR REVISIONS	INCH (METRIC)	CHK'D BY	TITLE QIK-FLECS IMPROVED WIPIING LENGTH FEMALE ASSEMBLY	
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	APP'D BY	SHEET NO. DATE 10F2 90/01/31	
		DESIGN DIMENSION (PRIMARY) <input type="checkbox"/> IN. <input checked="" type="checkbox"/> (MM) EQUIVALENT DIMENSION (SECONDARY) <input type="checkbox"/> IN. <input checked="" type="checkbox"/> (MM)	SCALE 4:1	SCALE	MOLLEX MOLEX EUROPE PART NO. SEE CHART DWG. NO. SDA-90573 SIZE B