

Base strip - PCV 6-16/ 8-G-10,16 - 1922543


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Header, Nominal current: 76 A, Number of positions: 8, Pitch: 10.16 mm, Color: green, Contact surface: Silver, Assembly: Soldering, The nominal current of 76 A applies in connection with connectors from the PC 16 family. 41 A are reached in connection with PC 6 connectors (50 A in accordance with UL).



Key commercial data

| | |
|--------------------------------------|--|
| Packing unit | 1 pc |
| GTIN |  4 017918 727093 |
| Weight per Piece (excluding packing) | 30.28 GRM |
| Custom tariff number | 85366990 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|-------------|----------|
| Pitch | 10.16 mm |
| Dimension a | 71.12 mm |

General

| | |
|----------------------------------|---------------|
| Range of articles | PCV 6-16/..-G |
| Rated voltage (III/3) | 630 V |
| Connection in acc. with standard | EN-VDE |
| Nominal current I_N | 76 A |
| Color | green |
| Number of positions | 8 |

Base strip - PCV 6-16/ 8-G-10,16 - 1922543

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260704 |
| eCl@ss 7.0 | 27440402 |
| eCl@ss 8.0 | 27440402 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002637 |
| ETIM 5.0 | EC002637 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211810 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11 | 39121409 |
| UNSPSC 12.01 | 39121409 |
| UNSPSC 13.2 | 39121409 |

Approvals

Approvals

Approvals

UL Recognized / SEV / cUL Recognized / GOST / CCA / GOST / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

Base strip - PCV 6-16/ 8-G-10,16 - 1922543

Approvals

| | | | |
|--------------------|-------|-------|-------|
| UL Recognized | | | |
| | B | C | D |
| Nominal current IN | 66 A | 66 A | 5 A |
| Nominal voltage UN | 300 V | 300 V | 600 V |

| | |
|--------------------|--------|
| SEV | |
| | |
| Nominal current IN | 76 A |
| Nominal voltage UN | 1000 V |

| | | | |
|--------------------|-------|-------|-------|
| cUL Recognized | | | |
| | B | C | D |
| Nominal current IN | 66 A | 66 A | 5 A |
| Nominal voltage UN | 300 V | 300 V | 600 V |

| | |
|------|--|
| GOST | |
|------|--|

| | |
|--------------------|--------|
| CCA | |
| | |
| Nominal current IN | 76 A |
| Nominal voltage UN | 1000 V |


| | |
|------|--|
| GOST | |
|------|--|

| | |
|------------------|--|
| cULus Recognized | |
|------------------|--|

Drawings

Base strip - PCV 6-16/ 8-G-10,16 - 1922543

Drilling diagram



Dimensioned drawing

