

## Specification Sheet

Part Number: 596-00652

Made with UV-stable inks and materials for durability and weather resistance.

Reflective properties to meet applicable NEC code requirements for reflective identification.

Supplied with an aggressive adhesive to ensure long life.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.



Solar Label, Printable, PHOTOVOLTAIC AC DISCONNECT, 3.75" x 1.0", PET, Red, 50/roll

Article Number 596-00652

Type PVACDIS-1

Color Red (RD)

Quantity Per roll

**Product Description**  
Designed in a one-across landscape format to fit into the compact TT130SMC thermal transfer printer, these labels allow for code-compliant marking of variable information including disconnecting means, breaker series and voltage data. Made with cross-laminated UV stable materials, labels are ideal for use in solar installation applications. Use with the TT130SMC or any HellermannTyton thermal transfer printer.

|                                |   |
|--------------------------------|---|
| Short Description              | Solar Label, Printable, PHOTOVOLTAIC AC DISCONNECT, 3.75" x 1.0", PET, Red, 50/roll |
| Global Part Name               | PVACDIS-1-840/281-RD  |
| Width W (Imperial)             | 1.0   |
| Width W (Metric)               | 25.4  |
| Thickness T (Metric)           | 64.0  |
| Height H (Imperial)            | 3.75  |
| Height H (Metric)              | 95.25   |
| Material                       | Type 840/281, Polyester, UV-stabilised, clear polyester laminate (840/281)          |
| Material Shortcut              | 840/281   |
| Adhesive                       | Acrylic   |
| Halogen Free                   | No  |
| UV Resistant (Yes/No)          | Yes   |
| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C)   |
| Operating Temperature          | -40°F to +302°F (-40°C to +150°C)   |

|                              |            |
|------------------------------|------------|
| Reach Compliant (Article 33) | Yes        |
| ROHS Compliant               | Yes        |
| Certification/Specification  | UL 969     |
| UL Recognized (US)           | Yes        |
| Package Quantity (Imperial)  | 50         |
| Package Quantity (Metric)    | 50         |
| Customs Number               | 3919102055 |
| Labels per Column            | 1          |
| Labels per Row               | 1          |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)