



# NLS-FM80

## FIXED MOUNT BARCODE SCANNER

### FEATURES

○ **Superior Scanning Performance**

Armed with Newland's sixth-generation of technology, this scanner can scan 1D and 2D barcodes and delivers stunning performance on decoding the EAN-13 barcode.

○ **High Motion Tolerance**

With 3.5m/s motion tolerance, the scanner can quickly capture moving goods, which greatly enhances efficiency.

○ **Multiple Status indicators**

6 kinds of status indicators show current working status of the scanner, including decoding, configuration, communication and abnormal status.

○ **Advanced Sense Mode**

The scanner activates a decode session every time it detects a barcode presented to it, and the target barcode shown in the window will not be read repeatedly.

○ **Large Scan Window**

Large scan window meets demands of goods with different sizes. When goods comes closer to the scan window, the scanner will conduct quick scanning.



CMOS



1D Barcode



2D Barcode



USB



Retail

# NLS-FM80

## Performance

Image Sensor		1280 * 1088 CMOS
Illumination		Red LED (614nm-624nm)
Symbologies	2D	PDF417, QR Code, Data Matrix, Aztec
	ID	Code 11, Code 128, Code 39, Code32 (Italian Pharma Code) GS1-128 (UCC/EAN-128), AIM 128, ISBT 128, Codabar, Code 93, UPC-A/UPC-E, Coupon, EAN-13, EAN-8, ISSN, ISBN, Interleaved 2/5, Matrix 2/5, Industrial 2/5, ITF-14, ITF-6, Standard 2/5, China Post 25, MSI-Plessey, Plessey, GS1 Databar, GS1 Composite
Resolution*		≥3mil (ID)
Typical Depth of Field*	EAN-13	0mm-140mm (13mil)
	EAN-13	50mm-90mm (5mil)
Scan Mode		Advanced sense mode
Min. Symbol Contrast*		15% (Code 128 10mil)
Scan Angle**		Roll: 360°, Pitch: ±55°, Skew: ±50°
Motion Tolerance*		350cm/s
Field of View		Horizontal 42.4°, Vertical 36°

## Physical

Interface		RS-232, USB
Operating Voltage		5VDC±5%
Rated Power Consumption	Operating	2W (typical), 2.5W (max.)
	Idle	1.25W
Current@5VDC	Operating	0.4A (typical), 0.5A (max.)
	Idle	0.25A
Dimensions		149 (W) × 78.5 (D) × 166.5 (H)mm
Weight		448.3g
Notification		Beep, LED indicator

## Environmenta

Operating Temperature	-20°C to 50°C (-4°F to 122°F)
Storage Temperature	-40°C to 70°C (-40°F-158°F)
Humidity	5% to 95% (non-condensing)
Ambient Light	0-100,000lux (natural light)
ESD	±15 KV (air discharge); ±8 KV (direct discharge)
Sealing	IP52

## Certificates

Certificates	FCC Part15 Class B, CE EMC Class B, RoHS
--------------	--

## Accessories

Cable	USB	Used to connect the scanner to a host device.
-------	-----	---

\*Test conditions: T=23°C; Illumination=300lux using incandescent lamp; sample printed barcodes made by Newland.

\*\*Test conditions: Scan Distance= (min. DOF + max. DOF) / 2; T=23°C; Illumination=300lux using incandescent lamp;

ID: EAN-13 (13mil).

Specifications are subject to change without notice.

Version: VI.4

### Newland AIDC

Add: No.1 Rujiang West Rd.,  
Mawei, Fuzhou, Fujian 350001, China  
Tel: +86-591-83979500  
Fax: +86-591-83979216  
Email: info@nlscan.com  
Web: www.newlandaidc.com

### North America&Latin America

Add: 46559 Fremont Blvd.,  
Fremont, CA 94538, USA  
Tel: +1 510 490 3888  
Fax: +1 510 490 3887  
Email: info@nlscan.com  
Web: www.newlandamerica.com

### Europe & Middle East

Add: Rolweg 25, 4104 AV Culemborg,  
The Netherlands  
Tel: +31 (0) 345 87 00 33  
Email: sales@newland-id.com  
Tech Support: tech-support@newland-id.com  
Web: www.newland-id.com

### Asia Pacific

Taiwan:  
Add: 7F-6, No. 268, Liancheng Rd.,  
Jhonghe Dist. 235, New Taipei City, Taiwan  
Tel: +886 2 7731 5388  
Email: info@newland-id.com.tw