

LUMAWISE | LUMAWISE LED Holders

TE Internal #: 2325811-2

LED Holders, Tridonic SLE-G6-SNC / Sharp Mega Zenigata GW5DGC**M04 / Sharp Mega Tuneable White GW6TGBJC50C,

LUMAWISE LED Holders

View on TE.com >



Connectors > Lighting Connectors > LED Holders > LED Holders, Z45



Compatible LED: Everlight EAHP2024 Series, Lumileds 1204, Lumileds 1204 GEN 3, Lumileds 1204CRSP, Lumileds 1205, Lumileds 1205 GEN 3, Lumileds 1205CRSP, Lumileds 1208, Lumileds 1208 CRSP, Lumileds 1208 GEN 3, Phillips FORTIMO LED SLM C PW G6 2024, Sharp Mega Tuneable White GW6TGBJC50C, Sharp Mega Zenigata GW5DGC**M04, Tridonic SLE-G6-SNC

Lighting Connector Features Included: No Driver on Board, Not Optic Compatible, Not Programmable, Zhaga Inspired

Operating Voltage: 60 VDC

Termination Method to Wire & Cable: Poke-In

Number of Positions: 1

All LED Holders, Z45 (11)

Features

Product Type Features

LED Holders Product Type	LED Holder
COB Substrate Thickness	1 mm
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Lighting Connector Features Included	No Driver on Board, Not Optic Compatible, Not Programmable, Zhaga Inspired
Number of Positions	1
Electrical Characteristics	
Operating Voltage	60 VDC



Compatible LED	Everlight EAHP2024 Series, Lumileds 1204, Lumileds 1204 GEN 3, Lumileds 1204CRSP, Lumileds 1205, Lumileds 1205 GEN 3, Lumileds 1205CRSP, Lumileds 1208, Lumileds 1208 CRSP, Lumileds 1208 GEN 3, Phillips FORTIMO LED SLM C PW G6 2024, Sharp Mega Tuneable White GW6TGBJC50C, Sharp Mega Zenigata GW5DGC**M04, Tridonic SLE-G6-SNC
Contact Features	
Contact Current Rating (Max)	3 A
Termination Features	
Termination Method to Wire & Cable	Poke-In
Housing Features	
Housing Material	PBT GF
Usage Conditions	
Operating Temperature Range	-40 - 105 °C[-40 - 105 °F]
Operation/Application	
Circuit Application	Power

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent




chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts






Also in the Series | LUMAWISE LED Holders



Customers Also Bought
















Documents

Product Drawings

LUMAWISE Z45 LED HOLDER 20X24

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2325811-2_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2325811-2_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2325811-2_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

LUMAWISE Z45 LED HOLDERS

English

Product Specifications

Application Specification

English

Application Specification

English

Application Specification

English

Agency Approvals

LED Holders

English

LED Holders CB Test Certificate to IEC 60838

English

LED Holders, Tridonic SLE-G6-SNC / Sharp Mega Zenigata GW5DGC**M04 / Sharp Mega Tuneable White GW6TGBJC50C, LUMAWISE LED Holders

