BKT Label Printing Scales





Sturdy and durable, BKT label printing scales are ideal for manufacturing, shipping and receiving, packing and distribution warehouses. The BKT has a built in printer that can print weight, QR codes, bar codes and labels in numerous languages. Software is included for personalized label design and formatting on computers. BKT scales consist of a sturdy ABS plastic indicator, cast aluminium base, and easy-to-clean stainless steel platform. Operation is simple using six buttons on the indicator, and results are readily visible on the backlit LCD. The indicator can be placed on a bench or attached to the included pillar. The BKT offer three platform sizes to accommodate large or small objects. RS-232 interface provide speedy connection to computers and printers.

Quickly produce custom labels and bar codes with the built-in printer



Features

- Vivid, backlit LCD easily visible in any lighting conditions
- Programmable backlight can be set to "always on," "always off" or "light only when weighing"
- Color-coded keys facilitate quick recognition of the most frequently used buttons
- Level indicator and adjustable feet ensure proper balance setup for optimum weighing results
- · Large, grade 304 stainless steel pan allows swift cleaning
- RS-232 interface is available to provide speedy connection to computers and printers
- · Rugged construction stands up to industrial use
- Sealed keypad protects against dirt and spills
- Overload protection helps prevent damage to internal components
- · Built in printer can print weight, QR codes, bar codes and labels in numerous languages
- Checkweighing with audible alarm
- · Memory accumulation totals results
- · Parts counting optimization automatically refines piece weight as parts are added
- Selectable digital filtering helps minimize effects of vibration and disturbances
- · Zero-tracking feature ensures display returns to zero reading
- Easy label creation/editing is possible on a computer using the included software
- Rechargeable battery included for operation almost anywhere
- Programmable auto power-off to save energy

Applications

- Weighing
- Parts counting
- Percentage weighing
- Checkweighing
- Dynamic / animal weighing
- Accumulation
- Display hold
- Peak hold
- Barcode / label printing

About ADAM:

For more than 45 years, professionals worldwide have relied on Adam Equipment for an extensive selection of dependable and affordable weighing equipment. Adam provides the right balance of speed, performance and value.

BKT Label Printing Scales



| Model | BKT 16a | BKT 35a | BKT 65a | BKT 130 a | BKT 260 a | BKT 165 a | BKT 165aH | BKT 330 a | BKT 330aH | BKT 660 a | BKT 1320a |
|-----------------------------|--|---|-----------------|------------------|------------------|---|-----------------|--------------------|------------------|--------------------|---|
| Capacity | 16lb / 8kg | 35lb / 16kg | 65lb / 30kg | 130lb / 60kg | 260lb / 120kg | 165lb / 75kg | 165lb / 75kg | 330lb / 150kg | 330lb / 150kg | 660lb / 300kg | 1320lb / 600kg |
| Readability | 0.0005lb / 0.2g | 0.001lb / 0.5g | 0.002lb / 1g | 0.005lb / 2g | 0.01lb / 5g | 0.01lb / 5g | 0.005lb / 2g | 0.02lb / 0.01kg | 0.01lb / 5g | 0.05lb / 0.02kg | 0.1lb / 0.05kg |
| Repeatability (S.D.) | 0.0005lb / 0.2g | 0.001lb / 0.5g | 0.002lb / 1g | 0.005lb / 2g | 0.02lb / 10g | 0.01lb / 5g | 0.005lb / 2g | 0.02lb / 0.01kg | 0.01lb / 5g | 0.05lb / 0.02kg | 0.1lb / 0.05kg |
| Linearity (+/-) | 0.001lb / 0.4g | 0.002lb / 1g | 0.005lb / 2g | 0.01lb / 5g | 0.02lb / 10g | 0.02lb / 10g | 0.01lb / 4g | 0.05lb / 0.02kg | 0.05lb / 10g | 0.1lb / 0.04kg | 0.2lb / 0.1kg |
| Pan Size | 11.8"x15.7" / 300x400mm | | | | | 15.7"x19.7" / 400x500mm | | | | | 23.6"x31.5" / 600x800mm |
| Weighing Units | g, kg, ct, lb, oz, dr, mm, T, tonne | | | | | | | | | | |
| Stabilization Time (sec) | 2 | | | | | | | | | | |
| Interface | RS-232 | | | | | | | | | | |
| Calibration | External calibration | | | | | | | | | | |
| Display | Backlit LCD with 1.3"/ 34mm -high digits | | | | | | | | | | |
| Power Supply | 12VDC 3A adapter / Internal rechargeable battery | | | | | | | | | | |
| Operating Tempera- ture | -10° to 40°C / 14° to 104°F | | | | | | | | | | |
| Housing | | ABS plastic indicator with die-cast aluminum base | | | | | | | | | |
| Overall Dim. | 11.8"x20.5"x26.8" / 300x520x680mm (wxdxh) | | | | | 15.7"x24.4"x33.9" / 400x620x860mm (wxdxh) | | | | | 23.6"x37"x35.4" / 600x940x- 900mm (wxdxh) |
| Net Weight | 18.7lb / 8.5kg | | | | | 29.8lb / 13.5kg | | | | | 58.4lb / 26.5kg |

Accessories

| Item number | Description |
|-------------|--------------------------------|
| 3074010266 | RS-232 cable (null-modem) |
| 600002028 | AdamDU Data Collection Program |
| 700200107 | Casters / wheels (set of 4) |
| 700660290 | Calibration certificate |
| 700660288 | |
| 400005615 | Labels - [800 per roll] |



Key Accessories

AdamDU Data

Collection Program Adam DU software connects a balance to the laboratory network, helping to achieve seamless data collection, transfer and analysis. DU features an easy-to-use interface with a main command window, allowing users to quickly collect information from up to eight Adam balances simultaneously using RS-232 or USB connections.

Casters / wheels (set of 4) Optional caster wheels provide

Optional caster wheels provide easy mobility for bench and floor scales. A brake lock prevents movement during use.



Supplied by

www.adamequipment.com

