GlobTek, Inc.	Drawing Title: Power Din Plug, 3P, Snap and Lock, Black, supplied in kit, ready to assemble	
www.globtek.com	Model No. High Power DC Connectors	
186 Veterans Drive,		
Northvale, NJ 07647		
Tel. (201) 784-1000	Part No./Ordering No. GTPWRDIN3LB	Rev A2
Fax (201) 784-0111		

In Addition to GlobTek Inc.'s renewed ISO9001:2008 - Quality Management System Certification, GlobTek Inc. is now certified to:

ISO13485:2003 - Medical Devices Quality Management System Certification ISO14001:2004 - Environmental Management System Certification

ISO Certificates are available online at http://www.globtek.com/iso-certificates/

The acceptance of this specification and use of the product described in this document indicates the acceptance and binding of the customer to Globtek TERMS AND CONDITIONS (attached to the end of this document), which supersede all other agreements, terms, and conditions (http://en.globtek.com/terms-and-conditions/).

Prop 65 Statement:https://en.globtek.com/prop-65-statement.pdf

Footnote:

GlobTek Inc. will not be liable for the safety and performance of these power supplies if unauthorized access and repair occurs. End user should consult applicable UL, CSA or EN standards for proper installation instruction.

Limitation of Use:

GlobTek products are intended for use with commercial, medical, and/or industrial equipment only. GlobTek product are not authorized for use as mission critical components in life support hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of GlobTek Inc.

Contents of this document are subject to change without prior notice.

Customer Approval of Specification:

Please approve, sign and send back to GlobTek so we can complete order processing. A delay in receipt of this form will delay delivery schedule.

Company Name:	Customer P/N:
Quote Number:	Date:
Authorized Representative Name:	Authorized Representative Signature:

PROPRIETARY INFORMATION

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC. © GlobTek, Inc. 2020 - 2023 guest /08/04/2023 9:49:40 AM CLONED FROM GTPWRDIN3LW

GlobTek, Inc.				
www.globtek.com				
186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Part No./Ordering No. <u>GTPWRDIN3LB</u>	Rev A2		

	1		REVISION HI				1	
REV	DESCRIPTION					SUB	DATE	APPROVED
A2	Add a link to the assembly instru	uctions P/N : PWRDINC	CONNECTOR_ASSEMBLY IN	ISTRUCTIO	ONS	QA	07/18/2022	QA
A1	Update the locking latch deta	ail				QA	06/21/2020	QA
А	Initial Release					DR	05/30/2020	QA
AGEN	NCY ONLINE DOCUMENTS							
RoHS	S/RoHS3 Declaration	<u>http</u>	s://www.globtek.com/pdf	/rohs_cert	:/01t3a000004vAUT	AA2		
REAC	CH Declaration	http	s://www.globtek.com/pdf	/iso_certif	icates/REACH.pdf			
Confli	ict Minerals Declaration	<u>http</u>	s://www.globtek.com/pdf	/conflict-m	ninerals.pdf			
Prop	65 Statement	http	s://en.globtek.com/prop-	65-statem	ent.pdf			
PXY	rating is based on 3rd party t	testing and custome	rs should check suitabilit	y and tes	t system level IPXY	rating befo	re ordering.	
Drawi	ng:							
			49.60±0.4					
			36.40±C.4					
		3	80.90±0.3					
		6	50±0.3					
]					
3.50	¢ ⊕ €	Ø10.00						
m	1 0 m	E E		i				
				سما				
	1200			1				
	13.00							
								
			000				0.0	
								15/
			000					
	ng Assembly detail: Standard different part #)	d and on this item:			Optional cover up	on request		
_1001	ical Specification:							
			Pin1:1+2:7.5A	A max	/54VDC Ma	x, Pin3	8:1.0A m	ax/54VC
Cu	Current /Voltage Pin 1: 1+2:7.5A max/54VDC Max, Pin3:1.0A max/54VD Pin 1: Signal wire designed for AWG24 max wire							
	Pin 2+3 contacts designed for AWG18 max wire							
Ine	ulation resistance		≥50MΩ 250V					
115		5		50				

PROPRIETARY INFORMATION

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC. © GlobTek, Inc. 2020 - 2023 guest /08/04/2023 9:49:40 AM CLONED FROM GTPWRDIN3LW

GlobTek, Inc.	Drawing Title: Power Din Plug, 3P, Snap and Lock, Black, supplied in kit, ready to assemble				
www.globtek.com	Model No. High Power DC Connectors				
186 Veterans Drive,					
Northvale, NJ 07647					
Tel. (201) 784-1000	Part No./Ordering No. GTPWRDIN3LB	Rev A2			
Fax (201) 784-0111					

Contact resistance	≤30 mΩ
Withstand voltage (pin to pin)	250VAC / 1min
Lifetime	≥5000
Operation Temperature	-20°C- 50°C
Mechanical Specification: Body: ABS, UL 94HB Rated Insert: Nylon, UL 94V-2 Rated Inner Shield: Copper Alloy, Nickel Plated Contacts: Brass, Silver Plated Insertion Force: 4.5KG Max Pull Force: 1.0-4.5KG unlocked, 4.5KG Min locked. Durability: 5000 cycles Color: GlobTek Black Each connector is packed in an individual bag Mates with: KPJX-3S-S KPJXHT-3S-S KPJXHT-3 KPJX-CM-3S KPJX-PM-3S-S KPJXHT-3 Assembly instructions P/N : PWRDINCOU https://globtek.secure.force.com/spec	S NNECTOR_ASSEMBLY INSTRUCTIONS:

GlobTek, Inc.	Drawing Title: Power Din Plug, 3P, Snap and Lock, Black, supplied in kit, ready to assemble			
www.globtek.com	Model No. High Power DC Connectors			
186 Veterans Drive,				
Northvale, NJ 07647				
Tel. (201) 784-1000	Part No./Ordering No. <u>GTPWRDIN3LB</u>	Rev A2		
Fax (201) 784-0111				

PACKAGING

Packing Spec P/N:	
Box Qty:	1000
Gift Box Size (mm):	
Gift Box Color:	White
Master Carton Size (mm):	TBD
Master Carton Cubic Volume (m ³):	0.00
Master GW (Kg):	kg
wt Ea. (Kg):	kg
wt Ea. (Kg):	kg
LABEL SPECS: ,	
PACK SPEC:	

PROPRIETARY INFORMATION
PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN
WRITING BY GLOBTEK, INC. © GlobTek, Inc. 2020 - 2023
guest /08/04/2023 9:49:40 AM CLONED FROM GTPWRDIN3LW
Page 4 of 4