



#### General ordering data

Order No.	1737100000
Part designation	VP M32-EXE SW
Version	Blanking plug, Polyamide, RAL 9005, External thread: M 32 x 1.5, IP 66
EAN	4008190956578
Qty.	20 pc(s).

#### General details

AF size 1	36 mm
Assembly temperature, max.	110 °C
Assembly temperature, min.	-40 °C
Class of protection with thread gasket	IP 68
External thread	M 32 x 1.5
Length	20.5 mm
Length of thread	15 mm
Material	Polyamide
Protection class	IP 66
RAL colour	RAL 9005
Type of cable gland	metric

#### Approvals

Approvals institutes	<b>n.a.</b>
----------------------	-------------

#### Classifications

ETIM 2.0	EC000032
ETIM 3.0	EC000032
eClass 4.1	27-14-12-10
eClass 5.0	27-14-91-10
eClass 5.1	27-14-91-10

#### Similar products

Order No.	Part designation	Version
1737070000	VP M16-EXE SW	Blanking plug, Polyamide, RAL 9005, External thread: M 16 x 1.5, IP 66
1737080000	VP M20-EXE SW	Blanking plug, Polyamide, RAL 9005, External thread: M 20 x 1.5, IP 66
1737090000	VP M25-EXE SW	Blanking plug, Polyamide, RAL 9005, External thread: M 25 x 1.5, IP 66
1737110000	VP M40-EXE SW	Blanking plug, Polyamide, RAL 9005, External thread: M 40 x 1.5, IP 66
1737120000	VP M50-EXE SW	Blanking plug, Polyamide, RAL 9005, External thread: M 50 x 1.5, IP 66
1737130000	VP M63-EXE SW	Blanking plug, Polyamide, RAL 9005, External thread: M 63 x 1.5, IP 66
1569380000	VP 11-EXE SW	Blanking plug, Polyamide, RAL 9005, External thread: PG 11, IP 66
1569390000	VP 13,5-EXE SW	Blanking plug, Polyamide, RAL 9005, External thread: PG 13.5, IP 66
1569400000	VP 16-EXE SW	Blanking plug, Polyamide, RAL 9005, External thread: PG 16, IP 66
1569410000	VP 21-EXE SW	Blanking plug, Polyamide, RAL 9005, External thread: PG 21, IP 66
1719300000	VP 29-EXE SW	Blanking plug, Polyamide, RAL 9005, External thread: PG 29, IP 66
1719310000	VP 36-EXE SW	Blanking plug, Polyamide, RAL 9005, External thread: PG 36, IP 66
1719320000	VP 42-EXE SW	Blanking plug, Polyamide, RAL 9005, External thread: PG 42, IP 66
1719330000	VP 48-EXE SW	Blanking plug, Polyamide, RAL 9005, External thread: PG 48, IP 66
1719280000	VP 7-EXE SW	Blanking plug, Polyamide, RAL 9005, External thread: PG 7, IP 66
1719290000	VP 9-EXE SW	Blanking plug, Polyamide, RAL 9005, External thread: PG 9, IP 66