



DIRECT MOUNT 5 dBi HORIZONTALLY POLARIZED OMNI

The Laird Technologies' OC18505 is a 1850-1990 MHz omnidirectional, collinear, vertically polarized array especially designed to compliment interior or exterior mounted wireless network systems. An integrated RF connector is imbedded in the antenna base cap for direct AP mounting. Special venting permits either upright or inverted orientation in outdoor locations. The antenna may also be pole-mounted when separation from the AP is required for optimum positioning.

FEATURES 


- Vertically polarized omnidirectional
- Rugged, lightweight and water resistant
- Direct to radio mounting
- PCS Band

MARKETS


- College campuses
- Airports
- Hospitals
- Transportation centers

PARAMETER	SPECIFICATION
Antenna Part Number	OC18505
Frequency Range	1850 - 1990 MHz
Gain	5 dBi
Polarization	Linear, Vertical
VSWR	1.7:1
3 dB Beamwidth - E-plane	Omnidirectional
3 dB Beamwidth - H-plane	33°
RF Connector	Type N, Male or Female, Standard
Power	50 Watts
Weight	0.16 kg
Radome	Polycarbonate, UV, White
Operational Temperature	-30°C to +70°C
Storage Temperature	-40°C to +85°C
Mounting	Connector Fixed or Mast Mount Kit

All antennas carry a 1-Year Warranty



H-plane 1.92 GHz



E-plane 1.92 GHz

global solutions: local support™

Americas: +1.847.839.6907
IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12
IAS-EUSales@lairdtech.com

Asia: +1.65.6.243.8022
IAS-AsiaSales@lairdtech.com

www.lairdtech.com

ANT-DS-OC18505 1110

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2010 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trade marks or registered trade marks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.