

FLAT BRAID IN LONG COIL, TINNED COPPER, 49.34 KCMIL

CATALOG NUMBER

FTCB20-25



CERTIFICATIONS







FEATURES

Braids in coil are mainly used for power distribution or earthing applications

Non-magnetic material

Tinned finish provides a theft-deterrent appearance

PRODUCT ATTRIBUTES

Article Number: 503540

Material: Copper

Finish: Tinned

Wire Diameter: 0.01"

Nominal Current: 150 A

Cross Section: 49.34 kcmil

Number of Wires: 1404

Length: 328'

Thickness: 0.07"

Width: 0.73"

ADDITIONAL PRODUCT DETAILS

Unit weight is per meter (3.28').

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 - Technical Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:

nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF

TRACER