

## Safe-IT USB 2.0 A to USB Mini-B Antibacterial Cable (M/M), White, 6 ft. (1.83 m)

MODEL NUMBER: U030AB-006-WH



USB cable with antibacterial properties connects mobile devices to your computer while helping to protect you from harmful bacteria.

### Features

#### Durable USB-A to USB Mini-B Cable Transfers Important Data at USB 2.0 Speeds

This USB cable (M/M) connects a digital camera, MP3 player, smartphone or other Mini-B peripheral with a 5-pin port to the USB-A port on your computer or laptop. It transfers data at USB 2.0 speeds up to 480 Mbps for use with low-speed and high-speed devices, including multimedia applications. The cable is also backward compatible with earlier USB generations.

#### Provides Extra Protection Against Certain Bacteria

The molded connectors and PVC jacket are constructed using an antibacterial material that is effective in inhibiting the growth of Escherichia coli (E. coli) and Staphylococcus aureus (staph). This added protection makes this cable an ideal solution for medical facilities, schools, businesses, restaurants/kitchens and anywhere else that needs extra protection against bacteria.

#### Premium Construction for Superior Performance

Manufactured with twisted 28 AWG data lines and 28 AWG power lines, the U030AB-003-WH also features molded gold-plated connectors and contacts that provide maximum conductivity and minimum data loss to guarantee a clear transmission free of interference. Integral strain relief gives the cable extra flexibility, reduces stress and helps the cable move freely without cracking or breaking loose from the connector.

#### White Jacket Helps Avoid Misidentification That Can Cause Costly Downtime

The cable has a white PVC jacket, which is easy to identify quickly in a crowded computer or hub and helps prevent the cable from becoming accidentally disconnected.

## Specifications

### OVERVIEW

UPC Code

037332260635

### Highlights

- Supports USB 2.0 speeds up to 480 Mbps to ensure efficient data transfers
- Made with antibacterial material proven effective in inhibiting the growth of E. coli and staph
- Foil and braid shielding protects against EMI/RFI noise that can distort or destroy data
- Gold-plated connectors and contacts for maximum conductivity and minimum data loss
- White jacket permits fast, easy identification in a crowded hub or computer

### Applications

- Connect a computer or laptop and a USB Mini-B peripheral in a home or office network
- Provide extra protection against bacteria to give cable installers and IT personnel peace of mind during installation

### Package Includes

U030AB-006-WH USB-A to USB Mini-B Antibacterial Cable (M/M), White, 6-ft. (1.83 m)

|                                      |                              |
|--------------------------------------|------------------------------|
| Technology                           | USB 2.0 (High Speed)         |
| Cable Type                           | Passive                      |
| <b>PHYSICAL</b>                      |                              |
| Material of Construction             | PVC                          |
| Cable Jacket Color                   | White                        |
| Cable Jacket Material                | PVC                          |
| Cable Jacket Rating                  | VW-1                         |
| Cable Outer Diameter (OD)            | 3.8MM                        |
| Wire Gauge (AWG)                     | 28/28                        |
| Cable Length (ft.)                   | 6                            |
| Cable Length (m)                     | 1.83                         |
| Cable Length (in.)                   | 72                           |
| Shipping Dimensions (hwd / in.)      | 9.00 x 7.00 x 0.50           |
| Shipping Weight (kg)                 | 0.05                         |
| Unit Packaging Type                  | Polybag                      |
| <b>ENVIRONMENTAL</b>                 |                              |
| Operating Temperature Range          | 14° to 122°F (-10° to 50°C)  |
| Storage Temperature Range            | 5° to 140°F (-15° to 60°C)   |
| Operating Humidity Range             | 0% to 90% RH, Non-Condensing |
| Storage Humidity Range               | 0% to 90% RH, Non-Condensing |
| <b>CONNECTIONS</b>                   |                              |
| Side A - Connector 1                 | USB A (MALE)                 |
| Side B - Connector 1                 | USB MINI-B 5-PIN (MALE)      |
| Connector Plating                    | Gold                         |
| Contact Plating                      | Gold                         |
| Connector Style                      | Straight                     |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                              |
| Antimicrobial                        | No                           |
| USB Specification                    | USB 2.0 (up to 480 Mbps)     |
| Antibacterial                        | Yes                          |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                              |
| Product Compliance                   | RoHS; REACH                  |

**WARRANTY & SUPPORT**

Product Warranty Period  
(Worldwide)

Lifetime limited warranty