



Product: <u>5302FE</u> ☑

Security & Sound, #18-4c, BC, Shielded, CMR

## **Product Description**

Security & Sound Cable, Riser-CMR, 4-18 AWG stranded bare copper conductors with polypropylene insulation, Beldfoil® shield and PVC jacket with ripcord

## **Technical Specifications**

Product Overview							
Suitable Applications:			Security	Security System, Intercom/PA, Audio/Speaker, Power-Limited Controls, Noisy Environment			
<b>Construction Details</b>							
Conductor							
Element	ement No. of Elements Size		Strandin	g Material			
Conductor(s)	4	18 AWG	7x26	BC - Bare Copper			
Insulation							
Element	Material	Nom. Thickness		lom. Insulation Diameter	Color Code		
Conductor(s)	PO - Polyolefin	PO - Polyolefin 0.009 in (0.23 r		.062 in (1.6 mm)	Black, Red, White, Green		
Outer Shield							
Shield Type	ield Type Material Co		overage	Drainwire Type			
Таре	Bi-Laminate (Alum+Poly) 100		00%	24 AWG (7x32) TC			
Outer Jacket							
Mater	ial Non	n. Thicknes	s Nom	. Diameter Ripcord			
PVC - Polyvinyl Chloride 0.017 in (0.43 mm) 0.188 in (4.78 mm) Yes							
Overall Cable Diameter (Nominal):			0.188 ir	n (4.78 mm)			

# **Electrical Characteristics**

## Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current	
Conductor(s)	6.5 Ohm/1000ft	27 pF/ft (89 pF/m)	48.5 pF/ft (159 pF/m)	4 Amps per conductor @ 25°C	

## Voltage

UL Voltage Rating 300 V (CMR)

## **Mechanical Characteristics**

### Temperature

<b>UL Temperature</b>	Operating
75°C	-20°C to +75°C

## Bend Radius

Stationary Min.	Installation Min.
1.9 in (48 mm)	1.9 in (48 mm)

Max. Pull Tension:	104 lbs (47.2 kg)
Bulk Cable Weight:	31 lbs/1000ft

## **Standards and Compliance**

Environmental Suitability:	Indoor - Riser, Indoor	
Flammability / Reaction to Fire:	UL 1666 Riser, FT4, IEC 60332-1-2	
CPR Compliance:	CPR Euroclass: Eca	
NEC / UL Compliance:	Article 800, CMR	
CEC / C(UL) Compliance:	CMG	
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) UKCA Mark	
UK Regulation Compliance:		
APAC Compliance:	China RoHS II (GB/T 26572-2011)	
Plenum Number:	6302FE	

#### **History**

Update and Revision:	Revision Number: 0.451 Revision Date: 03-04-2023	

## **Part Numbers**

### Variants

Item #	Color	Putup Type	Length	UPC/EAN	Footnote
5302FE.00152	Chrome	Reel	152 m	8719605008220	
5302FE.00305	Chrome	Reel	305 m	8719605008237	
5302FE.00U305	Chrome	Reel	305 m	8719605008244	
5302FE 0081000	Gray			612825336846	С
5302FE 008500	Gray			612825159551	
5302FE 008C250	Gray				
5302FE 008U1000	Gray			612825159537	
5302FE 008U500	Gray			612825159544	

### © 2023 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.