

RJ45 bending protection sleeve - VS-08-KS-H/GN - 1654756

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)




RJ45 bend protection sleeve, for pin inserts VS-08-ST-H11-RJ45 and VS-08-ST-H21-RJ45, for cable cross section up to 7 mm, color: green



Ethernet

Key commercial data

Packing unit	1 PCE
Minimum order quantity	5 PCE
GTIN	 4 017918 977818
Custom tariff number	39269097
Country of origin	CHINA

Technical data

Mechanical characteristics

External cable diameter	7 mm
Color	green
Ambient temperature (operation)	-40 °C ... 80 °C

Material data

Inflammability class according to UL 94	V0
Housing material	PA
Degree of protection	IP20

Classifications

ETIM

ETIM 2.0	EC000307
ETIM 3.0	EC001680

RJ45 bending protection sleeve - VS-08-KS-H/GN - 1654756

Classifications

ETIM

ETIM 4.0	EC001680
ETIM 5.0	EC001680

UNSPSC

UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501
UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501

eCl@ss

eCl@ss 4.0	27140906
eCl@ss 4.1	27140906
eCl@ss 5.0	27140915
eCl@ss 5.1	27140915
eCl@ss 6.0	27140915
eCl@ss 7.0	27439224

Accessories

Accessories

RJ45 male insert - VS-08-ST-H11-RJ45 - 1652716



RJ45 pin insert, CAT5e, 8-pos., shielded, IDC connection method, for litz wires AWG 27 ... 26, with strain relief

RJ45 male insert - VS-08-ST-H21-RJ45 - 1652729



RJ45 male insert, CAT6, 8-pos., shielded, IDC displacement connection, for litz wire AWG 25 ... 24 and solid wires AWG 24, with strain relief

Drawings

RJ45 bending protection sleeve - VS-08-KS-H/GN - 1654756

Dimensioned
drawing

RJ45
bending
protection
sleeve

© Phoenix Contact 2013 - all rights reserved
<http://www.phoenixcontact.com>