#### Main

Body type	Standard plug-in
Device short name	С
Series name	Heavy duty

## Complementary

- Comprehensi		
Line Rated Current	10 A	
Body Material	Zinc alloy	
Contact code designation	Q600 A600	
Contacts material	Silver alloy (Ag/Ni)	
Contact operation	Snap action	
Material	Viton fluorocarbon sealing gasket	
Maximum displacement angle	90 °	
Mounting location	Front Rear	
Specificity of operator	Standard pre-travel	
Switch actuation	CW and CCW	
Tilting angle	10 °	
Torque Value	4 lbf.in (0.45 N.m)	
Tripping angle	4 °	

## Environment

Ambient Air Temperature for Operation	-20185 °F (-2985 °C)
NEMA Degree of Protection	NEMA 1/2/4/6/6P/12/13
Product Certifications	CSA LR25490 class 3211 03 CE UL listed file E42259 CCN NKCR

### Ordering and shipping details

Category	21499-9007 C LIMIT SWITCHES
Discount Schedule	DS1
GTIN	00785901159865
Returnability	No
Country of origin	MX

#### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1

# Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	Product Environmental Profile
Contractual warranty	
Warranty	18 months

Warranty	18 months