



PIN OUT		
CN1	WIRE COLOR	CN2
1	ORANGE/WHITE	1
2	ORANGE	2
3	GREEN/WHITE	3
6	GREEN	6
4	BLUE	4
5	BLUE/WHITE	5
7	BROWN/WHITE	7
8	BROWN	8
SHELL	DRAIN WIRE	SHELL

Electrical test:
Open/short/intermittence: 100%

NO:	NAME	DESCRIPTION	QTY	UNIT
④	AL-Foil	Double-sided conductive aluminum foil ②	2	PCS
④	Molding	PVC 65P Color: see order code ②	NA	KG
④	CONNECTOR	RJ45 8P8C two fork 3u" gold plated with metal shield	2	PCS
④	CABLE	CAT5e F/UTP (26AWG*1PR)*4+D(AM)+A+PVC OD=5.2±0.3MM Color: see order code ②	NA	MM

WSW order code
AMJG0808-xxxx-xxB-26 ①

Cable length	Cable&Molding color
0030: 0.3M	BK: Black
0050: 0.5M	RD: Red
0100: 1.0M	YE: Yellow
0150: 1.5M	GN: Green
0200: 2.0M	GY: Grey
0300: 3.0M	BU: Blue
0500: 5.0M	WH: White
0700: 7.0M	BN: Brown
1000: 10M	
1500: 15M	

RoHS compliant
Unit: mm

Scale	Free				Date	Name	Customer-No.
TOLERANCE					Drawn	30.03.2017	Amy
					Approved	12.04.2022	Luca
		②	Change the plant	12.04.2022	Amy		
		①	Update the WSW order code	02.06.2017	Amy		
		①	Drawn	30.03.2017	Amy		
		ld.	Modification	Date	Name		
							ASSMANN WSW-No. ① AMJG0808-xxxx-xxB-26
							Drawing-No. ASS 7947 CA
							rev02
							Replace
							Sheet



ASS 7947 CA rev02