



- Protection level: IP67
- Temperature range: -30°C ... +80°C

| Cont. no | HARTING part no. | Type of cable | Dim. a[m] |
|----------|------------------|----------------------------------|-----------|
| 10 | 090700122250 | PVC, 3xAWG 18 + 16xAWG 22, black | 10 |
| 9 | 090700122255 | | 7.5 |
| 8 | 090700122251 | | 5 |
| 7 | 090700122254 | | 3 |
| 6 | 090700122253 | PUR, 3xAWG 18 + 16xAWG 22, black | 2 |
| 5 | 090700122200 | | 10 |
| 4 | 090700122205 | | 7.5 |
| 3 | 090700122201 | | 5 |
| 2 | 090700122204 | | 3 |
| 1 | 090700122203 | | 2 |

| | | | | | | | |
|------------------------------|--|----------------------------|---------------------|------------------|------------|--|--|
| All Dimensions in mm | | Tech. Character. | | Free size tol. | | According to production drawing | |
| All rights reserved | | Created by | Inspected by | Standardisation | Date | State | |
| Department HCS - RO | | BANCIUD Banciu | COSTEA Costea | MUNTEANV Muntean | 2020-04-15 | Final Release | |
| HARTING Customised Solutions | | Title har-SAB M12/8/5p PAC | | | | Doc-Key / ECM-Nr. 10068954/UGD/000/J 50000171068 | |
| D-32339 Espelkamp | | Type TB | Number 0907001222XX | | Rev. J | Page 1/1 | |