



NOTES:

① DATE CODE

*** WORKING DAY
 *** WORKING MONTH
 *** WORKING YEAR

② INSULATOR OVERHANGS ALL EXTERNAL EDGES.
 3. 6-32 UNC MIN. 2MM THREAD DEPTH
 4. PART IS COMPLIANT TO RoHS DIRECTIVE 2002/95/EC AND ELV 2000/53/EC.
 ⑤ SCREWS ARE PACKAGED INTO PLASTIC BAG AND SHIPPED WITH BACKPLATE.

47596-8838	WITH HALOGEN FREE	2.00(0.079")	5.6	4.22
47596-8833	WITH HALOGEN FREE	1.57(0.062")	5.17	3.8
PART NO.	DESCRIPTION	PCB THICKNESS	DIM.A	DIM.B

PARTS LIST			
ITEM NO	QTY	DESCRIPTION	MATERIAL
	1	TOP ASSY W/SCREWS(47596-***33 OR 47596-***38)	
①	1	115X BACK PLATE ASSY (47596-***23)	BACK PLATE(STEEL WITH NICKEL PLATING) INSULATOR(POLYCARBONATE FILM)
②	1	SHOULDER SCREW 6-32 (475976**1)	LOW CARBON STEEL WITH NICKEL PLATING
③	2	PANHEAD SCREW 6-32(475976**2)	LOW CARBON STEEL WITH NICKEL PLATING

ENTER DESCRIPTION
 EC NO: SH2012-0146
 DRWN: ZHANG11 2011/11/17
 CHKD:
 APPR: AYIN 2011/12/30

QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	
	mm	INCH
F _A =0	4 PLACES ± ---	± ---
F _C =0	3 PLACES ± ---	± ---
F _P =0	2 PLACES ± 0.13	± ---
	1 PLACE ± 0.25	± ---
	ANGULAR ± 1/2°	

DIMENSION STYLE		SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
MM ONLY		1.5:1	METRIC	
DRAWN BY	DATE	TITLE		
CHECKED BY	DATE	115X BACK PLATE ASSY WITH SCREWS FOR 1U SERVER		
APPROVED BY	DATE	MOLEX MOLEX INCORPORATED		
MATERIAL NO.	2010/07/09	DOCUMENT NO.	SD-47596-108	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SIZE	SHEET NO.	
		A3	1 OF 1	