

# AR181610CHTSST



Sample image

**Order symbol:** AR181610CHTSST

**Product nbr:** 8561084

**Description:** PC Enclosure


**Remarks:** Hinged transparent cover w/S.S. Lockable twist latch

**EAN:** 6418074067296

**El. number:**

- Finland:
- Denmark:
- Sweden:

**Including:** Hinged cover. Base with 10-32 brass inserts, latched cover with formed in place PUR gasket, stainless hinge pin. Quick release latches. Enclosure mounting foot kit. Accessory 10-32 screws for panel mounting.



Dimensions:	Height	Width	Depth
mm:	457	406	254
inch:	18	16	10

Accessories:	
APBP1816	PVC Back Panel (424 x 378)
ABP1816	Painted Steel Back Panel

**Materials:**

Material:	Polycarbonate
Base colour:	RAL 7035 -light grey
Cover colour:	Transparent
Gasket material:	Polyurethane

**Temperatures:**

Temperature °C (short term)::	-40 ... 140
Temperature °C (continuous):	-40 ... 80
Temperature °F (short term):	-40 ... 250
Temperature °F (continuous):	-40 ... 175

(424 x 378)

ASP1816	Aluminum Swing Panel (410 x 465 x 0)
ALBP1816	Aluminum Back Panel (424 x 378)
ADFP1816	Dead Front Panel w/ screws (412 x 465 x 0)
AMFL16	16" Mounting Flange Set
ASPK1816	Swing Panel Kit incl. Panel

**Rating:**

Ingress protection (EN 60529):	IP66; IP67;
Impact Resistance (EN 62262):	IK09;
Electrical insulation:	Not insulated
Halogen free (DIN/VDE 0472, Part 815):	1
UV resistance:	UL 508
Flammability Rating:	UL 508
Glow Wire Test (IEC 695-2-1) °C:	960 °C
NEMA Class	NEMA 4, 4X, 12 and 13

**Certificates:**

ARCA\_CertificateofCompliance