



Floor standing polyester enclosure, Thalassa PLA, plain door, completely sealed, 1000x500x320mm, IP65, IK10

NSYPLA1053G

Range	Thalassa
Product name	Thalassa PLA
Enclosure type	Multi-purpose
Product or component type	Suitable enclosure
Version	PLA
Nominal height	1000 mm
Nominal width	500 mm
Nominal depth	320 mm
Enclosure mounting	Floor-standing
Device composition	1 top part 1 bottom part

Complementary

Oompicinentary		
Body type	Sealed top and bottom part assembled with side parts	
Door type	Plain front	
Number of doors	1 door(s)	
Door opening side	Reversible (120 °)	
Lock type	4 points lock, 5 mm double-bar	
Accessibility for operation	Front Rear	
Removable parts	Door by hinges Rear panel by fixing element	
Material	Polyester reinforced with fibreglass	
Colour	Grey (RAL 7035)	
Standards	UL 508 A IEC 62208	
NEMA degree of protection	NEMA 13 NEMA 12 NEMA 3S NEMA 2 NEMA 1 NEMA 5 NEMA 3 NEMA 3X NEMA 3 NEMA 3R	
Product certifications	Veritas	

DNV Marine

Electrical insulation class	Class II		

Environment

IP degree of protection	IP65 conforming to IEC 60529 (completely sealed)
IK degree of protection	IK10 conforming to IEC 62262 (plain door)
Fire resistance	960 °C conforming to IEC 62208
Ambient air temperature for storage	-3590 °C

Packing Units

_	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	38.0 cm
Package 1 Width	53.0 cm
Package 1 Length	102.0 cm
Package 1 Weight	21.5 kg

Offer Sustainability

Sustainable offer status	Green Premium product REACh Declaration		
REACh Regulation			
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration		
Mercury free	Yes		
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information		
RoHS exemption information	Yes		
Environmental Disclosure	Product Environmental Profile		

Recommended replacement(s)