

Dwg. Number	Customer P/N	Times P/N	Length(L) in 'inch'
IE-00418-01	-	IBPS092-SMSM-6.0IN	6 +0.20/-0
IE-00418-02	-	IBPS092-SMSM-8.0IN	8 +0.20/-0
IE-00418-03	-	IBPS092-SMSM-10.0IN	10 +0.20/-0
IE-00418-04	-	IBPS092-SMSM-12.0IN	12 +0.24/-0

1.0 Scope

This drawing documents the construction and performance of PT- 092 cable assemblies manufactured by Times Microwave systems.

2.0 Cable Information

- 2.1 Cable to be PT-092
- 2.2 Jacket color to be Black
- 2.3 Jacket material to be Tefzel
- 2.4 Nominal cable impedance to be 50 ohms
- 2.5 Cable diameter to be 0.101" [2.57mm] (Nominal).

3.0 Connector Information

- 3.1 Forward Connector Type SMA (M) Straight Connector (SP150) Connector Body – Stainless Steel, Gold Plated Center Contact – Beryllium Copper, Gold Plated
- 3.2 After Connector

Type SMA (M) Straight Connector (SP150) Connector Body – Stainless Steel, Gold Plated Center Contact – Beryllium Copper, Gold Plated

Unless otherwise spec- ified, dimensions are in INCH. Tolerances are applicable when spec- ified.	Approvals			TIMES MICROWAVE SYSTEMS					
	Drawn	YA	10/28/22				www.timesmicrowave.com		
These drawings and specifications contain proprietary information	Checked			PT-092 CABLE ASSEMBLY					
which is the property of	Approved				(Space Assemblies)				
Times Microwave Systems.	Approveu			Size CAGE C		CODE Drawin		g No.:	
				A	68999		IE-00418-XX		
				Scale:	NA	Rev. ((A)	Sheet: 1 of 3	

THE REVISION STATUS OF ALL SHEETS OF THIS DRAWING IS THE SAME AS SHEET 1							
REV	DESCRIPTION DATE BY						
А	INITIAL RELEASE	10/28/22	YA				

4.0 Electrical Performance

- 4.1 Frequency range: DC 27GHz
- 4.2 Insertion loss & VSWR: As per below table,

Dwg. Number	Max. Insertion Loss in dB	Max. VSWR		
Dwg. Number	@ 27GHz	@ 27GHz		
IE-00418-01	1.06	1.35		
IE-00418-02	1.29	1.35		
IE-00418-03	1.53	1.35		
IE-00418-04	1.76	1.35		

5.0 Mechanical Performance

- 5.1 Overall Length to be specified length.
- 5.2 Minimum Bend radius is 0.437" [11.1mm].

6.0 Environmental Performance

- 6.1 Installation Temperature Range (-65°C to +150°C)
- 6.2 Storage Temperature Range (-65°C to +150°C)
- 6.3 Operating Temperature Range (-65°C to +150°C)

7.0 Marking

- 7.1 Markers are to be black text on White Color Marker Sleeve.
- 7.2 Marker Configuration to be:

Dwg. Number	Marker 1				
IE-00418-01	Times Microwave Systems IBPS092-SMSM-6.0IN \$\$\$\$\$				
IE-00418-02	Times Microwave Systems IBPS092-SMSM-8.0IN \$\$\$\$				
IE-00418-03	Times Microwave Systems IBPS092-SMSM-10.0IN \$\$\$\$\$				

Unless otherwise spec- ified, dimensions are in INCH. Tolerances are applicable when spec- ified.	Approvals			TIMES MICROWAVE SYSTEMS					
	Drawn	YA	10/28/22			www.timesmicrowave.com			
These drawings and specifications contain proprietary information	Checked			PT-092 CABLE ASSEMBLY					
which is the property of	Approved				(Space Assemblies)				
Times Microwave Systems.				Size	CAGE CODE 68999		Drawing No.: IE-00418-XX		
				A					
				Scale:	NA	Rev. ((A)	Sheet: 2 of 3	

