

# Eaton Internal Replacement Battery Cartridge (RBC) for Select 8kVA to 11kVA 9PX UPS Systems and EBMs

MODEL NUMBER: 744-A1976



UPS backup battery cartridge replaces the expired or aging internal battery in your Eaton 9PX UPS system or EBM.

## Features

### UPS Replacement Battery Cartridge for Select Eaton 9PX UPS Systems

This UPS backup battery replacement is compatible with Eaton's 9PX8K, 9PX8KHW, 9PX8KPM, 9PX8KTF5, 9PX11K, 9PX11KHW, 9PX11KPM, 9PX11KTF11, 9PX11KTF11M and 9PX11KTF5 UPS systems and 9PXEBM240RT extended battery module (EBM). Eaton UPS batteries have an expected lifespan of three to five years, so you should take proactive steps to avoid a dead battery and ensure continuous uptime.

### Comes Pre-Wired for Quick, Easy Installation

The sealed lead acid (SLA) 744-A1976 internal battery cartridge is hot-swappable, allowing you to install it without powering down any connected equipment. Built to function in a wide range of operating temperatures, the 744-A1976 has been carefully screened and certified to restore your UPS system's runtime performance to its original specifications. It is leakproof, requires no maintenance and comes pre-wired for quick and easy installation in your 9PX UPS system.

## Specifications

OVERVIEW	
UPC Code	037332282132
INPUT	
Input Phase	Single-Phase
BATTERY	
Battery Type	Valve Regulated Lead Acid (VRLA)

## Highlights

- Replacement battery backup for select Eaton 8kVA–11kVA 9PX UPS and EBMs
- Carefully screened and certified to restore UPS runtime to original specs
- Leakproof internal battery cartridge requires no regular maintenance
- Ships ready for immediate UPS installation to prevent downtime

## System Requirements

Compatible only with Eaton's 9PX8K, 9PX8KHW, 9PX8KPM, 9PX8KTF5, 9PX11K, 9PX11KHW, 9PX11KPM, 9PX11KTF11, 9PX11KTF11M and 9PX11KTF5 UPS systems and 9PXEBM240RT EBM

## Package Includes

744-A1976 Internal Replacement Battery Cartridge



Powering Business Worldwide

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States

Battery Replacement Description	Hot-swappable, user replaceable batteries. Re-use existing wiring harness.
Hot Swap Battery	Yes
<b>PHYSICAL</b>	
Unit Dimensions (hwd / in.)	4.720 x 11.420 x 6.300
Unit Weight (lbs.)	1.58
Unit Weight (kg)	0.72
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	32° to 104°F (0° to 40°C)
<b>APPLICATIONS</b>	
Used With	9PX8K, 9PX11K, 9PXEBM240RT, 9PX11KHW, 9PX11KPM, 9PX11KTF11, 9PX11KTF11M, 9PX11KTF5, 9PX8KHW, 9PX8KPM, 9PX8KTF5
<b>STANDARDS &amp; COMPLIANCE</b>	
Product Certifications	UL Listed; cUL Listed
Product Compliance	FCC (USA); CE (Europe)



Powering Business Worldwide

© 2023 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.