LABELMATE USA Label Handling Innovations

BOTTLEMATE-900 APPLICATORS

BOTTLEMATE-900 SERIES

If you are looking for a simple and versatile solution for applying labels to bottles, cans, jars or other cylindrical objects, look no further! BOTTLEMATE by Labelmate enables you to label all kinds of cylindrical objects by simply inserting the container and pressing a foot switch. Once the foot switch is activated the label is applied at over 4.5" per second, and most bottles are labeled in less than 2 seconds! The Heavy-Duty construction of BOTTLEMATE by Labelmate will withstand the most high volume production environments.



Technical Specifications	BOTTLEMATE-910P	BOTTLEMATE-910P-2
Labels per Bottle	1	1 or 2 ¹
Max Label Width (in)	9 (230-mm)	
Min Label Width (in)	0.25 (6-mm)	
Max Label Length (in)	18.5 (470-mm)	
Max Bottle Diameter (in)	6 (152-mm)	
Min Bottle Diameter (in)	0.5 (13-mm)	
Max Roll Diameter (in)	10 (254-mm)	
Core Diameter (in)	0.5 - 6 (13 - 152-mm)	
Label Types	Opaque & Transparent	
Max Speed (bottles per hour)	1,200	
Dimensions-HWD (in)	8 x 15.5 x 17 (203 x 394 x 432-mm)	
Weight (Ibs)	26 (11.8-kg)	
Input Power Specifications ²	120V or 220V	
Warranty	3 year limited warranty	
Available Options	 BMR-6 (Waste Liner Rewinder) AUTO-MATE (Automatic Labeling Option - Eliminates Need for Footswitch) BMC-1 (Label Counter) 	

1. BOTTLEMATE-910P-2 can apply a label to the front <u>and</u> back of bottles.

2. Specify desired voltage at time of order.