SIEMENS

Data sheet

US2:52BP7CT



30mm BlackMax, Epoxy Coated Corrosion Resistant Complete Metal Unit Illuminated Push-Pull Operator Full Voltage, 12V AC/DC Incandescent Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Plastic, Amber 3 Position Pull-Momentary/Push-Maintained UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

design of the product Actuator round Enclosure 1 number of command points 1 delivery state as a kit No Actuator product extension optional light source Yes color of the actuating element amber material of the actuating point plastic type of unlcking device pull-to-unlatch mechanism number of switching positions 3 Front ring standard material of the front ring standard material of the front ring metal color of the front ring standard material of the holder Metal Contract block/ lampholders 1 socket design BA 9s with lamp number of LED modules 0 General tachnical data product component of the operating voltage AC/DC • a the operating voltage AC/DC • of the operating voltage AC/DC • at DC rated value 12 v		
number of command points 1 delivery state as a kit No Actuator	design of the product	Actuator round
delivery state as a lot No Actuator	Enclosure	
Actuator Yes product extension optional light source Yes color of the actuating element amber material of the actuating element plastic ype of unlocking device pull-bunklath mechanism number of switching positions 3 Front ring Yes design of the front ring standard material of the foot ring metal color of the stront ring black Holder Metal Contract black/ lampholder standard socket design BA 9s with lamp number of LED modules 0 Contract black/ lampholders 1 Display number of LED modules 0 General technical data e of the toperating voltage AC/DC e of the toperating voltage AC/DC e of the toperating voltage IP20 e of the toparting voltage	number of command points	1
product extension optional light source Yes color of the actuating element amber material of the actuating element plastic type of unlocking device pull-c-unlatch mechanism number of switching positions 3 Front ring product component front ring Yes design of the front ring metal color of the front ring black Holder Metal color of the holder Metal Contract block/ lampholders 1 Display metal number of LB modules 0 Ceneral technical data product component product component No sight source Yes degree of pollution 1 type of voltage AC/DC surge voltage resistance rated value 4/kV of the operating voltage AC/DC Surge voltage resistance rated value 1/kV of the terminal IP20 IP20 IP20 IP20 operating voltage AC/DC Surge voltage resistance rated value 4/kV IP20 of the terminal IP20 IP2	delivery state as a kit	No
color of the actualing element plastic type of unlocking device pull-to-unlatch mechanism number of switching positions 3 Front ring Yes design of the front ring metal color of the front ring metal color of the front ring metal color of the front ring black Holder Metal Contact block/ lampholder Metal color of the operating voltage 0 General technical data 0 General technical data 0 General technical data Yes eight source Yes eight source Yes eight source Yes of the poprating voltage AC/DC e of the poprating voltage AC/DC e of the terminal IP20 operating voltage 4kV protoct colsas IP IP86 e of the terminal IP20 operating voltage 4kV supply voltage 13 V Supply voltage 4k/C	Actuator	
material of the actuating element plastic type of unlocking device pull-to-unlatch mechanism number of switching positions 3 Front ring Yes design of the front ring Standard material of the front ring Istandard color of the front ring metal color of the front ring Delack Holder material of the holder color of the front ring Delack Holder material of the holder contract block/ lampholder socket design socket design BA 9s with lamp number of LED modules 0 General technical data product component iamp transformer No ilight source Yes degree of pollution 1 type of voltage AC/DC of the operating voltage AC/DC of the terminal iP20 operating voltage for the voltage of the iterminal iP20	product extension optional light source	Yes
type of unlocking device pull-to-unlatch mechanism number of switching positions 3 Front ring product component front ring Yes design of the front ring standard metal color of the front ring metal color of the front ring material of the holder Metal Contact block / lampholder socket design BA 9s with lamp number of lampholders socket design 0 Contact block / lampholder mumber of lampholders 0 Contact block / lampholder ocheral technical data product component 0 elight source Yes degree of pollution 1 type of voltage AC/DC socket design 1 of the operating voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP68 IP20 IP	color of the actuating element	amber
number of switching positions 3 Front ring Yes design of the front ring standard material of the front ring metal color of the front ring black Holder material of the holder material of the holder Metal Contact block/ lampholder socket design socket design BA 9s with lamp number of LED modules 0 General technical data product component • lamp transformer No • light source Yes degree of pollution 1 type of voltage AC/DC • of the input voltage AC/DC • of the terminal iP20 operating voltage iP20 operating voltage iP3 v • at AC at 60 Hz rated value 12 13 V • at CC rated value 12 13 V • at CC rated value 12 13 V • at DC rated value 12 13 V <t< th=""><th>material of the actuating element</th><th>plastic</th></t<>	material of the actuating element	plastic
Front ring Yes design of the front ring standard material of the front ring metal color of the front ring black Holder Metal Contact block/lampholder socket design socket design BA 9s with lamp number of LED modules 0 General technical data 0 General technical data Ves gore of pollution 1 type of voltage AC/DC • of the input voltage AC/DC • of the terminal iP20 opperating voltage 12 13 V • at AC at 60 Hz rated value 12 13 V Supply voltage AC/DC • of the terminal iP20 opperating voltage 13 V • at AC at 60 Hz rated value 12 13 V • at AC at 60 Hz rated value 12 13 V Supply voltage AC/DC • at AC at 60 Hz rated value 12 13 V Supply voltage of the supply voltage of the light source AC/DC • at AC at 60 Hz rated value 12 13 V Supply voltage of the light source at A	type of unlocking device	pull-to-unlatch mechanism
product component front ring Yes design of the front ring standard material of the front ring metal color of the front ring black Holder Metal Contact block/ lampholder socket design mumber of lampholders 1 Display number of LED modules number of LED modules 0 General technical data general technical data product component elight source elight source Yes degree of pollution 1 type of voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 e of the terminal IP20 operating voltage 13 V e at AC at 60 Hz rated value 12 13 V e at DC rated value 12 13 V e at DC rated value 12 13 V ype of voltage of the supply voltage of the light source AC/DC supply voltage AC/DC	number of switching positions	3
design of the front ring standard material of the front ring metal color of the front ring black Holder material of the holder Contact block/ lampholder Metal Socket design BA 9s with lamp number of lampholders 1 Display 0 General tochnical data 0 General tochnical data 0 general tochnical data 1 product component 0 i light source Yes degree of pollution 1 type of voltage AC/DC of the input voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 of the terminal IP20 operating voltage 1 3 V surge of the supply voltage of the light source 4C/DC yppy ty voltage 13 V ypply voltage 13 V	Front ring	
material of the front ring metal color of the front ring black Holder Metal Contact block/ lampholder Socket design socket design BA 9s with lamp number of lampholders 1 Display 0 General technical data 0 general technical data 0 general technical data 0 of the operating voltage AC/DC • of the operating voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP20 operating voltage 1 JV • at AC at 60 Hz rated value 12 13 V • at C rated value 2 13 V • at C rated value 12 13 V • at D C rated value AC/DC supply voltage of the light source AC/DC	product component front ring	Yes
color of the front ring black Holder material of the holder material of the holder Metal Contact block/ lampholder socket design socket design BA 9s with lamp number of lampholders 1 Display 0 General technical data 0 product component 0 elight source Yes degree of pollution 1 type of voltage 6////2C of the input voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 of the terminal IP20 operating voltage 1.3 V • at AC at 60 Hz rated value 12 13 V • at C ated value 12 13 V • at DC rated value 12 13 V • ypep voltage of the light source AC/DC	design of the front ring	standard
Holder Metal Contact block/lampholder BA 9s with lamp socket design BA 9s with lamp number of lampholders 1 Display 0 General technical data 0 general technical data 7 Yes degree of pollution 1 type of voltage Yes degree of pollution 1 type of voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 of the terminal IP20 operating voltage 12 13 V otat Cat advalue 12 13 V eat CA t advalue 12 13 V eat DC rated value 12 13 V supply voltage of the light source AC/DC supply voltage of the li	material of the front ring	metal
material of the holder Metal Contact block/ lampholder BA 9s with lamp socket design BA 9s with lamp number of lampholders 1 Display 0 General technical data 0 product component 0 e lamp transformer No e light source Yes degree of pollution 1 type of voltage AC/DC e of the operating voltage AC/DC of the input voltage AC/DC of the terminal IP20 operating voltage IP20 operating voltage IP20 operating voltage IP30 operating voltage IP30 e at AC at 60 Hz rated value 12 13 V e at DC rated value 12 13 V e at DC rated value 12 13 V e at DC rated value AC/DC supply voltage of the light source at AC at 60 Hz AC/DC	color of the front ring	black
Contact block/ lampholder socket design BA 9s with lamp number of lampholders 1 Display 0 General technical data 0 groduct component 0 e lamp transformer No e light source Yees degree of pollution 1 type of voltage AC/DC of the operating voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 operating voltage 1 ot at AC at 60 Hz rated value 12 13 V e at DC rated value 12 13 V supply voltage of the light source AC/DC supply voltage AC/DC	Holder	
socket design BA 9s with lamp number of lampholders 1 Display 0 number of LED modules 0 General technical data 0 product component 0 • lamp transformer No • light source Yes degree of pollution 1 type of voltage AC/DC • of the operating voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 operating voltage 12 13 V • at AC at 60 Hz rated value 12 13 V • at DC rated value 12 13 V	material of the holder	Metal
number of lampholders 1 Display 0 number of LED modules 0 General technical data 0 product component 0 • lamp transformer No • light source Yes degree of pollution 1 type of voltage AC/DC • of the operating voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 operating voltage 12 13 V • at DC rated value 12 13 V supply voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz AC/DC	Contact block/ lampholder	
Display number of LED modules 0 General technical data	socket design	BA 9s with lamp
number of LED modules 0 General technical data 0 product component 0 e lamp transformer No e light source Yes degree of pollution 1 type of voltage AC/DC e of the operating voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 e of the terminal IP20 operating voltage I e at AC at 60 Hz rated value 12 13 V supply voltage AC/DC supply voltage of the supply voltage of the light source AC/DC	number of lampholders	1
General technical data product component • lamp transformer • light source degree of pollution 1 type of voltage • of the operating voltage • of the input voltage AC/DC surge voltage resistance rated value 4 kV protection class IP • of the terminal IP20 operating voltage • at AC at 60 Hz rated value 12 13 V • at DC rated value type of voltage of the light source AC/DC	Display	
product component No • light source Yes degree of pollution 1 type of voltage AC/DC • of the operating voltage AC/DC • of the input voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 operating voltage 12 13 V • at AC at 60 Hz rated value 12 13 V Supply voltage AC/DC type of voltage of the light source AC/DC	number of LED modules	0
Image: Image in the start of	General technical data	
• light source Yes degree of pollution 1 type of voltage 1 • of the operating voltage AC/DC • of the input voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 operating voltage 1 • at AC at 60 Hz rated value 12 13 V • at DC rated value 12 13 V supply voltage IP20	product component	
degree of pollution 1 type of voltage AC/DC • of the operating voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 operating voltage	lamp transformer	No
type of voltage AC/DC • of the operating voltage AC/DC • of the input voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 operating voltage IP20 operating voltage I2 13 V • at AC at 60 Hz rated value 12 13 V Supply voltage I2 13 V supply voltage of the supply voltage of the light source AC/DC	light source	Yes
• of the operating voltageAC/DC• of the input voltageAC/DCsurge voltage resistance rated value4 kVprotection class IPIP66• of the terminalIP20operating voltage-• at AC at 60 Hz rated value12 13 V• at DC rated value12 13 Vsupply voltage of the supply voltage of the light sourceAC/DCsupply voltage of the light source at AC at 60 HzAC/DC	degree of pollution	1
• of the input voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 operating voltage I2 13 V • at AC at 60 Hz rated value 12 13 V • at DC rated value 12 13 V supply voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz AC/DC	type of voltage	
surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 operating voltage IP20 • at AC at 60 Hz rated value 12 13 V • at DC rated value 12 13 V Supply voltage IP20 type of voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz IP20	 of the operating voltage 	AC/DC
protection class IP IP66 • of the terminal IP20 operating voltage IP20 • at AC at 60 Hz rated value 12 13 V • at DC rated value 12 13 V Supply voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz AC/DC	 of the input voltage 	AC/DC
• of the terminal IP20 operating voltage - • at AC at 60 Hz rated value 12 13 V • at DC rated value 12 13 V Supply voltage - type of voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz -	surge voltage resistance rated value	4 kV
operating voltage 12 13 V • at AC at 60 Hz rated value 12 13 V • at DC rated value 12 13 V Supply voltage 12 13 V type of voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz 4C/DC	protection class IP	IP66
• at AC at 60 Hz rated value 12 13 V • at DC rated value 12 13 V Supply voltage 12 13 V supply voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz AC/DC	of the terminal	IP20
• at DC rated value 12 13 V Supply voltage type of voltage of the supply voltage of the light source supply voltage of the light source at AC at 60 Hz AC/DC	operating voltage	
Supply voltage type of voltage of the supply voltage of the light source AC/DC	• at AC at 60 Hz rated value	12 13 V
type of voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz AC/DC	• at DC rated value	12 13 V
supply voltage of the light source at AC at 60 Hz	Supply voltage	
	type of voltage of the supply voltage of the light source	AC/DC
• rated value 12 V	supply voltage of the light source at AC at 60 Hz	
	rated value	12 V

supply voltage of the light source at DC	
rated value	12 V
Connections/ Terminals	
type of electrical connection	screw-type terminals
 of modules and accessories 	Screw-type terminal
tightening torque of the screws in the bracket	20 N·m
tightening torque [lbf·in] with screw-type terminals	8 8 lbf-in
Lamp	
type of light source	filament lamp
color of the light source	clear
Safety related data	
touch protection against electrical shock	finger-safe
Ambient conditions	
ambient temperature	
during operation	-35 +70 °C
during storage	-40 +85 °C
Installation/ mounting/ dimensions	
shape of the installation opening	round
Certificates/ approvals	
Further information	
Siemens has decided to exit the Russian market (see here). https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business Siemens is working on the renewal of the current EAC certificates. Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus). Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875 Information- and Downloadcenter (Catalogs, Brochures,) https://www.siemens.com/ic10 Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52BP7CT Cax online generator http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52BP7CT Service&Support (Manuals, Certificates, Characteristics, FAQs,) https://support.industry.siemens.com/cs/ww/en/ps/US2:52BP7CT Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros,)	

last modified:

5/31/2021 🖸