## SIEMENS

## Data sheet

## US2:52BP7JTXB



30mm BlackMax, Epoxy Coated Corrosion Resistant Complete Metal Unit Illuminated Push-Pull Operator Transformer type, 480V AC LED Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Plastic, Amber 3 Position Pull-Momentary/Push-Maintained UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

| design of the product                                     | Actuator round            |  |
|---|---------------------------|--|
| Enclosure   |                           |  |
| number of command points                                  | 1                         |  |
| delivery state as a kit                                   | No                        |  |
| Actuator  |                           |  |
| product extension optional light source                   | Yes                       |  |
| color of the actuating element                            | amber                     |  |
| material of the actuating element                         | plastic                   |  |
| type of unlocking device                                  | pull-to-unlatch mechanism |  |
| number of switching positions                             | 3                         |  |
| Front ring  |                           |  |
| product component front ring                              | Yes                       |  |
| design of the front ring                                  | standard                  |  |
| material of the front ring                                | metal                     |  |
| color of the front ring                                   | black                     |  |
| Holder  |                           |  |
| material of the holder                                    | Metal                     |  |
| Contact block/ lampholder                                 |                           |  |
| socket design   | BA 9s with LED            |  |
| number of lampholders                                     | 1                         |  |
| Display   |                           |  |
| number of LED modules                                     | 1                         |  |
| General technical data                                    |                           |  |
| product component   |                           |  |
| lamp transformer  | Yes                       |  |
| light source  | Yes                       |  |
| degree of pollution                                       | 1                         |  |
| type of voltage   |                           |  |
| <ul> <li>of the operating voltage</li> </ul>              | AC                        |  |
| <ul> <li>of the input voltage</li> </ul>                  | AC                        |  |
| surge voltage resistance rated value                      | 4 kV                      |  |
| protection class IP                                       | IP66                      |  |
| <ul> <li>of the terminal</li> </ul>                       | IP20                      |  |
| Supply voltage  |                           |  |
| type of voltage of the supply voltage of the light source | AC                        |  |
| supply voltage of the light source at AC at 60 Hz         |                           |  |
| rated value   | 6 V                       |  |
| Inputs/ Outputs   |                           |  |
| output voltage 1 of the lamp transformer rated value      | 6 V                       |  |
| Connections/ Terminals                                    |                           |  |

| type of electrical connection   | screw-type terminals   |
|---|--|
| <ul> <li>of modules and accessories</li> </ul>  | Screw-type terminal  |
| tightening torque of the screws in the bracket  | 20 N·m   |
| tightening torque [lbf·in] with screw-type terminals  | 8 8 lbf·in   |
| amp   |  |
| type of light source  | LED  |
| color of the light source   | yellow   |
| Safety related data   |  |
| touch protection against electrical shock   | finger-safe  |
| Ambient conditions  |  |
| ambient temperature   |  |
| during operation  | -35 +70 °C   |
| during storage  | -40 +85 °C   |
| nstallation/ mounting/ dimensions   |  |
| shape of the installation opening   | round  |
| Certificates/ approvals   |  |
| urther information  |  |
| Siemens has decided to exit the Russian market (see here).  |  |
| https://press.siemens.com/global/en/pressrelease/siemens-wind-  |  |
| Siemens is working on the renewal of the current EAC certif<br>Please contact your local Siemens office on the status of validity<br>EAC relevant market (other than the sanctioned EAEU members) | of the EAC certification if you intend to import or offer to supply these products to an |
| Information on the packaging  |  |
| https://support.industry.siemens.com/cs/ww/en/view/109813875  |  |
| Information- and Downloadcenter (Catalogs, Brochures,)  |  |
| https://www.siemens.com/ic10  |  |
| Industry Mall (Online ordering system)<br>https://mall.industry.siemens.com/mall/en/en/Catalog/product?ml   | lfb=US2:52BP7JTXB  |
| Cax online generator  |  |
| http://support.automation.siemens.com/WW/CAXorder/default.as  | px?lang=en&mlfb=US2:52BP7JTXB  |
| Service&Support (Manuals, Certificates, Characteristics, FA   |  |
| https://support.industry.siemens.com/cs/ww/en/ps/US2:52BP7JT  |  |
| Image database (product images, 2D dimension drawings, 3<br>http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=U   |  |
|   |  |

last modified:

5/31/2021 🖸