

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD		STORAGE TEMPERATURE RANGE		-10 °C T0 + 60 °C (NOTES 2)		
RATING	OPERATING TEMPERATURE RANGE	-45 °C T0 +125 °C (NOTES 1)		APPLICABLE CONNECTOR		
	VOLTAGE	150 V AC		DF9B-25P-1V (68)		
	CURRENT	0.5 A				
SPECIFICATIONS						
ITEM	TEST METHOD	REQUIREMENTS		QT	AT	
GENERAL EXAMINATION			CONSTRUCTION			
VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.				
MARKING		CONFIRMED VISUALLY.				
ELECTRIC CHARACTERISTICS						
CONTACT RESISTANCE	100 mA (DC OR 1000 HZ).	50 mΩ MAX.		X	-	
INSULATION RESISTANCE	100 V DC.	500 MΩ MIN.		X	-	
VOLTAGE PROOF	250 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.				
MECHANICAL CHARACTERISTICS						
MECHANICAL OPERATION		100 TIMES INSERTIONS AND EXTRACTIONS.		① CONTACT RESISTANCE: 50 mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		
SHOCK		490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		
ENVIRONMENTAL CHARACTERISTICS						
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -65 → 5 TO 35 → 125 → 5 TO 35 °C TIME 30 → 10 TO 15 → 30 → 10 TO 15 min UNDER 5 CYCLES.		① CONTACT RESISTANCE: 50 mΩ MAX. ② INSULATION RESISTANCE: 500 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		
DAMP HEAT (STEADY STATE)		EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.		① CONTACT RESISTANCE: 50 mΩ MAX. ② INSULATION RESISTANCE: 500 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.		① CONTACT RESISTANCE: 50 mΩ MAX. ② NO HEAVY CORROSION.		
SULPHUR DIOXIDE		EXPOSED IN 10 PPM FOR 96 h. (TEST STANDARD: JEIDA-39)		① CONTACT RESISTANCE: 50 mΩ MAX. ② NO HEAVY CORROSION.		
HEAT RESISTANCE OF SOLDERING		[RECOMMENDED TEMPERATURE PROFILE] «SOLDERING AREA» MAX 250 °C, 220 °C FOR 60 SECONDS MAX. 150 TO 180 °C, 90 ~ 120 SECONDS. MAXIMUM TWICE ACTION IS ALLOWED UNDER THE SAME CONDITION. [RECOMMENDED MANUAL SOLDERING CONDITION] SOLDERING IRON TEMPERATURE 380 °C SOLDERING TIME : WITHIN 3 SECONDS.		NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.		
SOLDERABILITY		SOLDERING TEMPERATURE: 245 ± 5 °C DURATION OF IMMERSION : SOLDERING FOR 3 SECONDS		A NEW UNIFORM COATING OF SOLDER SHALL COVER MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED.		
REMARKS						
NOTES 1 : INCLUDING THE TEMPERATURE RISE BY CURRENT. NOTES 2 : STORAGE IS DEFINED AS LONG-TERM STORAGE OF UNUSED PRODUCTS. APPLY OPERATION TEMPERATURE RANGE TO PRODUCTS MOUNTED ON PCB WITHOUT POWER SUPPLY. UNLESS OTHERWISE SPECIFIED , REFER TO JIS C 5402 .						
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE		
△				APPROVED	MO .NAKAMURA	06 .01 .26
				CHECKED	TS .MIYAZAKI	06 .01 .26
				DESIGNED	TY .001	06 .01 .25
				DRAWN	HK .MURAKAMI	06 .01 .25
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.		ELC4-084767-06		
SPECIFICATION SHEET		PART NO.	DF9B-25S-1V (68)			
HIROSE ELECTRIC CO., LTD.		CODE NO.	CL540-0133-4-68			
					△	1/1