

TE Internal #: 3-352152-0

Hard Metric Backplane Connectors, PCB Mount Receptacle, ≤1 Gb

/s, 22 Column, 5 Row, Traditional Backplane, 110 Position, 2 mm [.


078 in] Centerline

View on TE.com >



Connectors > PCB Connectors > Backplane Connectors > Hard Metric Backplane Connectors >

Hard Metric Backplane Receptacle Connector: Mezzanine, 2mm











PCB Connector Assembly Type: PCB Mount Receptacle

Data Rate: ≤1 Gb/s

Number of Columns: 22

Number of Rows: 5

Backplane Architecture: Traditional Backplane

All Hard Metric Backplane Receptacle Connector: Mezzanine, 2mm (27)

#### **Features**

### **Product Type Features**

Backplane Interface Type	2mm HM
PCB Connector Assembly Type	PCB Mount Receptacle
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Signal Positions	110
Number of Columns	22
Number of Rows	5
Backplane Architecture	Traditional Backplane
Number of Positions	110
PCB Mount Orientation	Right Angle



### Signal Characteristics

Data Rate	≤1 Gb/s
Body Features	
Primary Product Color	Gray
Contact Features	
CompactPCI Designation	None
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Phosphor Bronze
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Material Thickness	.76 μm[30 μin]
Contact Current Rating (Max)	1.5 A
Mechanical Attachment	
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	Glass Filled Polyester
Centerline (Pitch)	2 mm[.078 in]
Usage Conditions	
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Operation/Application	
Circuit Application	Signal
Packaging Features	
Packaging Method	Tube

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235)



SVHC > Threshold:

Pb (13% in Component Part)

Article Safe Usage Statements:

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content

Not Low Halogen - contains Br or Cl > 900 ppm.

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## **Customers Also Bought**

















### **Documents**

Product Drawings
Z-PACK/B F-HDR 110P

English

Product Specifications

Application Specification

Hard Metric Backplane Connectors, PCB Mount Receptacle, ≤1 Gb/s, 22 Column, 5 Row, Traditional Backplane, 110 Position, 2 mm [.078 in] Centerline



English

Product Environmental Compliance

**Product Compliance** 

English

**Product Compliance** 

English