



NOTES

1. MATERIAL: COPPER ALLOY, t=0.25mm
2. FINISH: PRE-TIN PLATED
3. RECOMMENDED LENGTH OF WIRE STRIP: 5.0-5.6

PRE-RELEASE
REFERENCE
USE ONLY

| NO. | ENG. NO. | TYPE | DESCRIPTION | CABLE SIZE(mm ²) AVS, AVSS | DIMENSION | | | |
|-----|------------|------|--------------------------|---|-----------|-----|-----|-----|
| | | | | | W1 | H1 | W2 | H2 |
| 1 | 35407-6702 | S | .090 SEALED FEMALE TER'L | 0.3 - 0.5 | 2.5 | 2.2 | 5.1 | 4.2 |
| 2 | 35407-6802 | M | .090 SEALED FEMALE TER'L | 0.85-1.25 | 2.6 | 3.0 | 5.2 | 4.7 |

| | | | | | |
|---|--------|--|---------|--------------------------|-----------------|
| THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION | | CURRENT REV DESC: OBSOLETE PART NUMBER | | molex | |
| DIMENSION UNITS | SCALE | | | | |
| mm | 5:1 | | | .090 SEALED FEMALE TER'L | |
| GENERAL TOLERANCES (UNLESS SPECIFIED) | | | | | |
| | MM | INCH | | | |
| 4 PLACES | ± | ± | | | |
| 3 PLACES | ± | ± | | | |
| 2 PLACES | ± | ± | | | |
| 1 PLACE | ± 0.25 | ± | | | |
| 0 PLACES | ± | ± | | | |
| ANGULAR TOL ± 1.0° | | | | | |
| DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS | | THIRD ANGLE PROJECTION | DRAWING | SERIES | MATERIAL NUMBER |
| | | | A3-SIZE | 35407 | SEE TABLE |
| | | EC NO: 655042 | | DOCUMENT NUMBER | |
| | | DRWN: ABHISP1 | | SD-35407-001 | |
| | | CHK'D: GGA | | DOC TYPE | |
| | | APPR: GGA | | PSD | |
| | | INITIAL REVISION: | | DOC PART | |
| | | DRWN: BCYOON | | 001 | |
| | | APPR: CWLEE | | REVISION | |
| | | 1998/04/10 | | E | |
| | | 1998/04/10 | | | |
| | | CUSTOMER | | SHEET NUMBER | |
| | | GENERAL MARKET | | 1 OF 1 | |