



Gloss Meter PCE-GM 60Plus



Gloss Meter PCE-GM 60Plus-ICA for non-stationary use / Measurement up to 200 gloss points / 60° Measurement geometry/ 3.5" TFT display / short measuring time of 0.5 seconds

The gloss tester PCE-GM 60Plus is a measuring device for the determination of gloss on different materials. During the measurement, the gloss tester picks up the reflection of emitted light. The light is emitted directly by the gloss tester. Part of the light is then reflected off the surface to be measured and part of the light is absorbed by the surface. Thanks to the reflected light, the gloss tester then calculates the degree of gloss and displays it clearly on the TFT display.

The gloss tester is used in areas where it is essential that individual products always have the same appearance and texture and properties. In this way, complaints and associated costs are avoided. In addition, the external reputation of companies with consistent quality and consistent products is respected or improved. Thus, the gloss tester PCE-GM 60Plus can assist you.

- ▶ 60° measuring geometry
- ▶ 3.5" TFT touchscreen display
- ▶ Built-in rechargeable battery
- ▶ Quick 0.5 second measuring time
- ▶ 0 ... 200 GU gloss measurement range
- ▶ Measuring accuracy ± 1.5 GU
- ▶ Self-calibration possible using included calibration plate
- ▶ Chromaticity fulfills CIE 1931 2° under a CIE illuminant C
- ▶ Reflective gloss measurement per ISO 2813, GB/T 9754, ASTM D523 and ASTM D2457 standards
- ▶ Light source: D65
- ▶ Wave length: 400-700 nm

Subject to change

Specifications

Measuring geometry	60°
Display	3.5" TFT touchscreen display
Standards	ISO 2813
	GB/T 9754
	ASTM D523
	ASTM D2457
Measuring aperture	10 x 25 mm / 0.4 x 1.0 in
Measuring range	0 ... 200 GU
Readability	1 GU
Repeatability	±1 GU
Reproducibility	±1 GU
Chromaticity	Fulfills CIE 1931 2° under a CIE illuminant C
Measuring accuracy	±1.5 / ±1.5%
Measuring time	0.5 second
Dimensions	160 x 75 x 90 mm / 6.3 x 3 x 3.5 in
Weight	350 g / 0.78 lb
Menu languages	English, Chinese
Power supply	3200-mAh Li-ion rechargeable battery
Data interface	USB / RS-232
Operating temperature	0 ... 40°C / 32 ... 104°F
Storage temperature	-20 ... 50°C / -4 ... 122°F
Relative humidity	< 85% RH (non-condensing)

More information

Manual



More product info



Similar products



Subject to change