



ROHS NUMBER

SHELL	A±0.38	B±0.12	C±0.10	D±0.25	E±0.07	Gold Flash	0.76µ Gold	1.27µ Gold
09	30.81	24.99	16.96	16.21	10.96	D09S90C4G*00LF	D09S90C6G*00LF	D09S90C8G*00LF
15	39.14	33.32	25.18	24.54	19.18	D15S90C4C*00LF	D15S90C6G*00LF	D15S90C8G*00LF
25	53.03	47.04	39.12	38.25	33.12	D25S90C4C*00LF	D25S90C6G*00LF	D25S90C8G*00LF
37	69.32	63.50	55.68	54.71	49.68	D37S90C4C*00LF	D37S90C6G*00LF	D37S90C8G*00LF

Threaded ØT M3 = L  
Threaded ØT 4-40 = X

GENERAL CHARACTERISTICS AND ROHS INFORMATIONS:  
SEE DRAWING C01-8646-0001

mat'l. code		surface <input checked="" type="checkbox"/> ISO 1302		tolerance <input checked="" type="checkbox"/> ISO 406 <input type="checkbox"/> ISO 1101		projection		product family D-SUB		
ltr	ecn no	dr	date	tolerances unless otherwise specified		mm		title		
K	ELX-I-21654	AB	2015-10-26	angles	linear	.0±0.1	←	FEMALE DELTA-D LOW PROFILE STRAIGHT PRESS FIT		
L	ELX-I-24020	AAB	2016-06-06	0°±2'		.00±0.1		scale 2:1	dwg no sheet 1 of 1 size	
						.000±0.1			C01-8646-0310 A3	
sheet index		revision	L	Amphenol FCI		type		Product Customer Drawing		
	sheet	1								