

BOX TERMINAL 4 PCS. ACCESSORY FOR: 3VA5/6 400/600



Model	
product brand name	SETRON
product designation	accessories
Accessories	Box terminal
General technical data	
designation / of the terminal	TS1.5
Connections according IEC	
connectable conductor cross-section	
• for copper cable / stranded / minimum	35 mm ²
• for copper cable / stranded / maximum	300 mm ²
stripped length	26.5 mm
tightening torque / when using copper cables	
• stranded	35 - 95 mm ² : 16 Nm, 120 - 300 mm ² : 28 Nm
• finely stranded	35 - 95 mm ² : 16 Nm, 120 - 240 mm ² : 28 Nm
Connections according UL	
stripped length	1.05 in
connectable conductor cross-section	
• for copper cable / stranded / minimum	1/0 AWG
• for copper cable / stranded / maximum	500 kcmil
• for copper cable / finely stranded / minimum	1/0 AWG
• for copper cable / finely stranded / maximum	500 kcmil
tightening torque / when using copper cables	
• stranded	1/0 - 4/0: 140 lb-in 250 -500 kcmil: 248 lb-in
• finely stranded	1/0 - 4/0: 140 lb-in 250 -500 kcmil: 248 lb-in

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9474-0JA13>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA9474-0JA13>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9474-0JA13

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

last modified:

7/5/2022

