

ZSCT SERIES

Current Transformer





Description

The ZSCT series is a current transformer used with Littelfuse relays to detect low levels of earth-leakage current.

Accessories



CBLTP

Twisted-pair wire for connection to CT. Order in desired length in meters.

Specifications

 Current Rating
 ZSCT5: 5:0.05 A

 ZSCT30: 30:0.05A

 Accuracy
 ZSCT5: 3% @ 0.01 VA

 ZSCT30: 3% @ 0.06 VA

Frequency 50 to 400 Hz **Insulation Level** 600V

Operating Temperature $-40 \text{ to } 55^{\circ} \text{ C (-40 to } 131^{\circ} \text{ F)}$

Application MP8000

 Wire Gauge
 0.05-3.3mm² (12-30 AWG)

 Tightening Torque
 0.5 N-m

Certification UL, cUL, CE


Compliance RoHS, IEC 61869-2, ANSI/IEEE C57.13

Note: One frequency response may be extended for specific product families $\label{eq:constraint} % \begin{subarray}{ll} \end{subarray} \$

Ordering Information

| ORDERING NUMBER | TURNS RATIO | WINDOW SIZE, ID | WEIGHT |
|-----------------|----------------|-----------------|--------------------|
| ZSCT5-31 | 100:1 | 31mm (1.22 in) | 117.9 g (0.26 lbs) |
| ZSCT5-88 | 100:1 | 88mm (3.46 in) | 499.0 g (1.10 lbs) |
| ZSCT30-31 | 600:1 | 31mm (1.22 in) | 113.4 g (0.25 lbs) |









ZSCT SERIES


Dimensions and Mounting Diagram Inches [millimeters]


Mount the ZSCT5-31 and ZSCT30-31 using M5 or #10 screws. Mount the ZSCT5-88 using M6 or 1/4" screws.







TOP VIEW AND MOUNTING DETAIL





FRONT VIEW





SIDE VIEW

Disclaimer Notice — Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/product-disclaimer.