


ORDERING INFORMATION



TECHNICAL SPECIFICATION

INSULATOR MATERIAL : SELF EXTINGUISHING THERMOPLASTIC (UL94 VO)  
 CONTACT MATERIAL : COPPER ALLOY  
 MAXIMUM VOLTAGE : 500 V rms.  
 NOMINAL CURRENT : 3A AT 20°C  
 INSULATION RESISTANCE : > 1000 MΩ  
 CLIMATIC CATAGORY : -55°C TO +125°C / 21 DAYS EXPOSURE TO- INDUSTRIAL ENVIRONMENT HUMIDITY TEST AS HE-14.  
 CONTACT RESISTANCE : < 20mΩ

NOTES :  
 1. THE PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-47-004

mat'l. code				surface		tolerance		projection		product family			
REF TECH SPEC				ISO 1302		ISO 406 ISO 1101				8614			
ltr	ecn no	dr	date	tolerances unless otherwise specified		.0±0.1		MM		title			
C	I06-0124	MKV	2002-07-12	angles		linear				FEMALE SHORTING PLUG (CLOSED)			
D	I06-0126	MKV	2003-06-07	0°±1°				scale -		dwg no			
E	I06-0127	MKV	2004-09-29	dr		MINI K VANDANATH		1998-12-06		sheet 1 of 1 size			
F	I06-0116	AB	2006-07-20	enr		JAI.K.A		1998-12-06		A3			
G	ELX-I-19435	GMA	2014-11-15	chr		GREGAR.M		2016-07-15		C-8614-0085			
H	ELX-I-24519	GMA	2016-07-15	appd		BIJU K P		2016-07-15		type Product Customer Drawing			
sheet index		revision sheet		C	D	E	F	G	H				
				1	1	1	1	1	1				