

Printed-circuit board connector - MSTBO 2,5/ 4-4 ST SET - 2707961

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Set, consisting of COMBICON headers and PCB terminal blocks for 6 x 4-pos. (24-pos.), color: green



Key commercial data

| | |
|--------------------------------------|----------|
| Packing unit | 1 1 |
| Weight per Piece (excluding packing) | 38.3 GRM |
| Custom tariff number | 85366990 |
| Country of origin | Germany |

Technical data

| | |
|---------------------|---------------------------------------|
| Product type | Printed circuit board housing |
| Approval | CSA |
| | VDE report with production monitoring |
| | IECEE CB Scheme |
| | GOST |
| | UL Recognized |
| | cUL Recognized |
| | CCA |
| | cULus Recognized |
| Rated voltage (IEC) | 320 |
| Rated current (IEC) | 12 |
| Mounting type | Soldering |
| Number of positions | 4 |
| Pitch | 5 mm |
| Levels | Single-level |
| Type of locking | Without |

Printed-circuit board connector - MSTBO 2,5/ 4-4 ST SET - 2707961

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27180401 |
| eCl@ss 4.1 | 27180401 |
| eCl@ss 5.0 | 27180506 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260704 |
| eCl@ss 7.0 | 27440402 |
| eCl@ss 8.0 | 27440402 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001031 |
| ETIM 3.0 | EC001031 |
| ETIM 4.0 | EC002638 |
| ETIM 5.0 | EC002638 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 31261501 |
| UNSPSC 7.0901 | 31261501 |
| UNSPSC 11 | 31261501 |
| UNSPSC 12.01 | 31261501 |
| UNSPSC 13.2 | 31261501 |

Approvals

Approvals

Approvals

CSA / VDE Gutachten mit Fertigungsüberwachung / IECCEB Scheme / UL Recognized / cUL Recognized / CCA / cULus Recognized


Ex Approvals


Approvals submitted


Approval details


Printed-circuit board connector - MSTBO 2,5/ 4-4 ST SET - 2707961


Approvals

| | | |
|---|-------|-------|
| CSA  | | |
| | B | D |
| mm ² /AWG/kcmil | 28-12 | 28-12 |
| Nominal current I _N | 10 A | 10 A |
| Nominal voltage U _N | 300 V | 300 V |

| | |
|---|-------|
| VDE Gutachten mit Fertigungsüberwachung  | |
| Nominal current I _N | 8 A |
| Nominal voltage U _N | 250 V |

| | |
|---|-------|
| IECEE CB Scheme  | |
| Nominal current I _N | 8 A |
| Nominal voltage U _N | 250 V |


| | | |
|---|-------|-------|
| UL Recognized  | | |
| | B | D |
| mm ² /AWG/kcmil | 30-12 | 30-12 |
| Nominal current I _N | 15 A | 10 A |
| Nominal voltage U _N | 300 V | 300 V |

| | | |
|--|-------|-------|
| cUL Recognized  | | |
| | B | D |
| mm ² /AWG/kcmil | 30-12 | 30-12 |
| Nominal current I _N | 15 A | 10 A |
| Nominal voltage U _N | 300 V | 300 V |

Printed-circuit board connector - MSTBO 2,5/ 4-4 ST SET - 2707961

Approvals

| | |
|--------------------------------|-------|
| CCA | |
| Nominal current I _N | 8 A |
| Nominal voltage U _N | 250 V |



Accessories

Accessories

Coding element

Coding section - CR MSTBO-G1 - 2199618



Coding section