S43B0C-P30MFD0-650S

series_b, type_s4



General information

| Part number | S43B0C-P30MFD0-650S | |
|-------------------|---------------------|--|
| Termination | solder | |
| Size | 3 | |
| Locking principle | push | |
| Coding | 0_key | |
| Cable Diameter | cable_mini_65 | |
| Cable outlet | bend_relief | |



Contact insert description

| Number of contacts | 30 |
|----------------------|--------|
| Contact type | pins |
| Contact diameter | 07mm |
| Insulator material | peek |
| Wire cross section | 26_awg |
| Termination | solder |
| Termination diameter | 06mm |

 $reverse_gender_on_request$

Technical information

| Max. creepage and air clearance distance | 06 _{mm} | 12_mm |
|--|------------------|---------------|
| Nominal current single contact | 06_a | iec_60512_5_2 |
| Test voltage | 09_kv_ac | sae_13441 |

safety_text

Mechanical and environmental data

| Degree of protection* | ip68 |
|-----------------------|----------|
| Operating temperature | 40_120_c |
| Mating cycles | 5000 |

mated

Material and surface treatments

| Housing | m_chrome |
|---------|---------------|
| Contact | cu_alloy_gold |
| | |

safety_text_2 ul_text illustrative_text