

**Data sheet | Item number: 279-508**

Double-deck terminal block; 4-conductor through terminal block; L; suitable for Ex i applications; internal commoning; conductor entry with violet marking; for DIN-rail 35 x 15 and 35 x 7.5; 1.5 mm<sup>2</sup>; 1,50 mm<sup>2</sup>; gray



[www.wago.com/279-508](http://www.wago.com/279-508)




Color:



Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



## Data

### Electrical data

#### Ratings per IEC/EN

|                               |   |
|-------------------------------|---|
| Ratings per                   | IEC/EN 60947-7-1  |
| Nominal voltage (III/3)       | 500 V   |
| Rated impulse voltage (III/3) | 6 kV  |
| Rated current                 | 18 A  |
| Legend (ratings)              | (III / 3) ≙ Overvoltage category III / Pollution degree 3 |

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



### Ratings per UL

|                                |         |
|--------------------------------|---------|
| Approvals per                  | UL 1059 |
| Rated voltage UL (Use Group C) | 600 V   |
| Rated current UL (Use Group C) | 10 A    |

### Ratings per CSA

|                                 |                 |
|---------------------------------|-----------------|
| Approvals per                   | CSA 22.2 No 158 |
| Rated voltage CSA (Use Group C) | 600 V           |
| Rated current CSA (Use Group C) | 10 A            |

### Power Loss

|  |                |
|--|----------------|
| Power loss, per pole (potential)                             | 0.593 W        |
| Rated current $I_N$ for specified power loss                 | 18 A           |
| Resistance value for specified, current-dependent power loss | 0.002 $\Omega$ |

### Connection data

|                            |   |
|----------------------------|---|
| Connection points          | 4 |
| Total number of potentials | 1 |
| Number of levels           | 2 |

### Connection 1

|                                 |  |
|---------------------------------|--|
| Connection technology           | CAGE CLAMP®                                  |
| Actuation type                  | Operating tool                               |
| Connectable conductor materials | Copper                                       |
| Solid conductor                 | 0.08 ... 1.5 mm <sup>2</sup> / 28 ... 16 AWG |
| Fine-stranded conductor         | 0.08 ... 1.5 mm <sup>2</sup> / 28 ... 16 AWG |
| Strip length                    | 8 ... 9 mm / 0.31 ... 0.35 inches            |
| Wiring direction                | Front-entry wiring                           |

### Physical data

|                                   |                      |
|-----------------------------------|----------------------|
| Width                             | 4 mm / 0.157 inches  |
| Height                            | 85 mm / 3.346 inches |
| Depth from upper-edge of DIN-rail | 39 mm / 1.535 inches |

Subject to changes. Please also observe the further product documentation!



## Mechanical Data

|                   |                 |
|-------------------|-----------------|
| Potential marking | L               |
| Design            | horizontal type |
| Mounting type     | DIN-35 rail     |
| Marking level     | Side marking    |

## Material Data

|                             |  |
|-----------------------------|--|
| Note (material data)        | Information on material specifications can be found here |
| Color                       | gray   |
| Material group              | I  |
| Insulation material         | Polyamide (PA66)   |
| Flammability class per UL94 | V0   |
| Fire load                   | 0.146 MJ   |
| Weight                      | 7.8 g  |

## Environmental requirements

|                                  |                 |
|----------------------------------|-----------------|
| Processing temperature           | -35 ... +85 °C  |
| Continuous operating temperature | -60 ... +105 °C |

## Commercial data

|                       |                                  |
|-----------------------|----------------------------------|
| Product Group         | 1 (Rail Mounted Terminal Blocks) |
| eCl@ss 10.0           | 27-14-11-20                      |
| eCl@ss 9.0            | 27-14-11-20                      |
| ETIM 8.0              | EC000897                         |
| ETIM 7.0              | EC000897                         |
| PU (SPU)              | 50 pcs                           |
| Packaging type        | box                              |
| Country of origin     | CN                               |
| GTIN                  | 4050821237266                    |
| Customs tariff number | 85369010000                      |

## Environmental Product Compliance

|                        |                         |
|------------------------|-------------------------|
| RoHS Compliance Status | Compliant, No Exemption |
|------------------------|-------------------------|

Subject to changes. Please also observe the further product documentation!



## Approvals / Certificates

### General approvals

| Logo | Approval                                     | Additional Approval Text | Certificate name |
|------|--|--------------------------|------------------|
|      | <b>CCA</b><br>DEKRA Certification B.V.       | EN 60947                 | NTR NL-7081      |
|      | <b>CSA</b><br>DEKRA Certification B.V.       | C22.2 No. 158            | 70133738         |
|      | <b>KEMA/KEUR</b><br>DEKRA Certification B.V. | EN 60947                 | 2160584.04       |
|      | <b>UL</b><br>Underwriters Laboratories Inc.  | UL 1059                  | E45172           |

### Declarations of conformity and manufacturer's declarations

| Logo | Approval  | Additional Approval Text | Certificate name |
|------|---|--------------------------|------------------|
|      | <b>EU-Declaration of Conformity</b><br>WAGO GmbH & Co. KG | -                        | -                |
|      | <b>UK-Declaration of Conformity</b><br>WAGO GmbH & Co. KG | -                        | -                |

### Approvals for marine applications

| Logo | Approval  | Additional Approval Text | Certificate name |
|------|---|--------------------------|------------------|
|      | <b>ABS</b><br>American Bureau of Shipping               | -                        | 20-HG1941090-PDA |
|      | <b>DNV GL</b><br>Det Norske Veritas, Germanischer Lloyd | -                        | TAE00001V2       |

## Required accessories

### End plate

| End plate  |  |  |
|--|--|--|
| <b>Item no.: 279-519</b><br>End and intermediate plate; 2 mm thick; orange |  | <a href="http://www.wago.com/279-519">www.wago.com/279-519</a> |
| <b>Item no.: 279-518</b><br>End and intermediate plate; 2 mm thick; gray   |  | <a href="http://www.wago.com/279-518">www.wago.com/279-518</a> |

## Optional accessories

### Mounting

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



|                          |   |  |
|--------------------------|---|--|
| Cover carrier            |   |  |
| <b>Item no.: 709-168</b> | Cover carrier; Type 2; incl. fixing/retaining screws and knurled nut; suitable for 283 to 285 Series rail-mounted terminal blocks; suitable for 279 to 281 Series double- and triple-deck terminal blocks; suitable for 780 to 785, 775, 776 and 777 Series TOPJOB® rail-mounted terminal blocks; suitable for 280 Series sensor and actuator terminal blocks; suitable for 282 Series disconnect/test terminal blocks for transformer circuits; gray | <a href="http://www.wago.com/709-168">www.wago.com/709-168</a> |
| Cover                    |   |  |
| <b>Item no.: 709-154</b> | Cover; Type 2; suitable for cover carrier, type 2; 1 m long; transparent  | <a href="http://www.wago.com/709-154">www.wago.com/709-154</a> |
| Mounting accessories     |   |  |
| <b>Item no.: 209-106</b> | Mounting carrier; for isolated mounting on DIN 35 rails; gray   | <a href="http://www.wago.com/209-106">www.wago.com/209-106</a> |
| <b>Item no.: 249-116</b> | Screwless end stop; 6 mm wide; for DIN-rail 35 x 15 and 35 x 7.5; gray  | <a href="http://www.wago.com/249-116">www.wago.com/249-116</a> |
| Ferrule                  |   |  |
| Ferrule                  |   |  |
| <b>Item no.: 216-101</b> | Ferrule; Sleeve for 0.5 mm <sup>2</sup> / AWG 22; uninsulated; electro-tin plated; silver-colored   | <a href="http://www.wago.com/216-101">www.wago.com/216-101</a> |
| <b>Item no.: 216-102</b> | Ferrule; Sleeve for 0.75 mm <sup>2</sup> / AWG 20; uninsulated; electro-tin plated; silver-colored  | <a href="http://www.wago.com/216-102">www.wago.com/216-102</a> |
| <b>Item no.: 216-103</b> | Ferrule; Sleeve for 1 mm <sup>2</sup> / AWG 18; uninsulated; electro-tin plated   | <a href="http://www.wago.com/216-103">www.wago.com/216-103</a> |
| <b>Item no.: 216-203</b> | Ferrule; Sleeve for 1 mm <sup>2</sup> / AWG 18; insulated; electro-tin plated; red  | <a href="http://www.wago.com/216-203">www.wago.com/216-203</a> |
| <b>Item no.: 216-202</b> | Ferrule; Sleeve for 0.75 mm <sup>2</sup> / 18 AWG; insulated; electro-tin plated; gray  | <a href="http://www.wago.com/216-202">www.wago.com/216-202</a> |
| <b>Item no.: 216-201</b> | Ferrule; Sleeve for 0.5 mm <sup>2</sup> / 20 AWG; insulated; electro-tin plated; white  | <a href="http://www.wago.com/216-201">www.wago.com/216-201</a> |
| <b>Item no.: 216-301</b> | Ferrule; Sleeve for 0.25 mm <sup>2</sup> / AWG 24; insulated; electro-tin plated; yellow  | <a href="http://www.wago.com/216-301">www.wago.com/216-301</a> |
| <b>Item no.: 216-302</b> | Ferrule; Sleeve for 0.34 mm <sup>2</sup> / 22 AWG; insulated; electro-tin plated; light turquoise   | <a href="http://www.wago.com/216-302">www.wago.com/216-302</a> |
| Testing and measuring    |   |  |
| Testing accessories      |   |  |
| <b>Item no.: 209-170</b> | Test plug adapter; 8.3 mm wide; for 4 mm Ø test plugs; suitable for 1.5 mm <sup>2</sup> - 10 mm <sup>2</sup> tbs; gray  | <a href="http://www.wago.com/209-170">www.wago.com/209-170</a> |
| <b>Item no.: 280-404</b> | Test plug adapter; 5 mm wide; for test plug (2.3 mm Ø); suitable for 1.5 mm <sup>2</sup> - 4 mm <sup>2</sup> tbs; gray  | <a href="http://www.wago.com/280-404">www.wago.com/280-404</a> |

Subject to changes. Please also observe the further product documentation!



## Tool

### Operating tool

|  |  |
|--|--|
| <b>Item no.: 210-648</b><br>Operating tool; Blade: 2.5 x 0.4 mm; with a partially insulated shaft; angled; short | <a href="http://www.wago.com/210-648">www.wago.com/210-648</a> |
| <b>Item no.: 210-647</b><br>Operating tool; Blade: 2.5 x 0.4 mm; with a partially insulated shaft; multicoloured | <a href="http://www.wago.com/210-647">www.wago.com/210-647</a> |
| <b>Item no.: 210-719</b><br>Operating tool; Blade: 2.5 x 0.4 mm; with a partially insulated shaft                | <a href="http://www.wago.com/210-719">www.wago.com/210-719</a> |

## Protective warning marker

### Cover

|  |  |
|--|--|
| <b>Item no.: 279-415</b><br>Protective warning marker; 5-pole; with high-voltage symbol, black; yellow | <a href="http://www.wago.com/279-415">www.wago.com/279-415</a> |
|--|--|

## Push-in type wire jumper

### Jumper

|  |  |
|--|--|
| <b>Item no.: 249-123</b><br>Push-in type wire jumper; 0.75 mm <sup>2</sup> ; insulated; 180 mm long; black | <a href="http://www.wago.com/249-123">www.wago.com/249-123</a> |
| <b>Item no.: 249-126</b><br>Push-in type wire jumper; 0.75 mm <sup>2</sup> ; insulated; 110 mm long; black | <a href="http://www.wago.com/249-126">www.wago.com/249-126</a> |
| <b>Item no.: 249-127</b><br>Push-in type wire jumper; 0.75 mm <sup>2</sup> ; insulated; 250 mm long; black | <a href="http://www.wago.com/249-127">www.wago.com/249-127</a> |
| <b>Item no.: 249-125</b><br>Push-in type wire jumper; insulated; 60 mm long; black                         | <a href="http://www.wago.com/249-125">www.wago.com/249-125</a> |

## Insulation stop

### Insulation stop

|  |  |
|--|--|
| <b>Item no.: 279-470</b><br>Insulation stop; 0.08 - 0.2 mm <sup>2</sup> "s" (0.14 mm <sup>2</sup> "f-st"); 5 pieces/strip; white | <a href="http://www.wago.com/279-470">www.wago.com/279-470</a> |
| <b>Item no.: 279-471</b><br>Insulation stop; 0.25 mm <sup>2</sup> ; 5 pieces/strip; dark gray                                    | <a href="http://www.wago.com/279-471">www.wago.com/279-471</a> |

## Marking accessories

### Marker carrier

|   |  |
|---|--|
| <b>Item no.: 279-529</b><br>Adaptor; gray | <a href="http://www.wago.com/279-529">www.wago.com/279-529</a> |
|---|--|

### Double marker carrier

|   |  |
|---|--|
| <b>Item no.: 209-128</b><br>Adaptor; gray | <a href="http://www.wago.com/209-128">www.wago.com/209-128</a> |
|---|--|

### Marker

|  |  |
|--|--|
| <b>Item no.: 2009-114/000-002</b><br>WMB-Inline; for Smart Printer; 2000 pieces on roll; stretchable 4 - 4.2 mm; plain; snap-on type; yellow | <a href="http://www.wago.com/2009-114/000-002">www.wago.com/2009-114/000-002</a> |
|--|--|

Subject to changes. Please also observe the further product documentation!



|  |  |
|--|--|
| <b>Item no.: 2009-114/000-005</b><br>WMB-Inline; for Smart Printer; 2000 pieces on roll; stretchable 4 - 4.2 mm; plain; snap-on type; red    | <a href="http://www.wago.com/2009-114/000-005">www.wago.com/2009-114/000-005</a> |
| <b>Item no.: 2009-114/000-007</b><br>WMB-Inline; for Smart Printer; 2000 pieces on roll; stretchable 4 - 4.2 mm; plain; snap-on type; gray   | <a href="http://www.wago.com/2009-114/000-007">www.wago.com/2009-114/000-007</a> |
| <b>Item no.: 2009-114/000-023</b><br>WMB-Inline; for Smart Printer; 2000 pieces on roll; stretchable 4 - 4.2 mm; plain; snap-on type; green  | <a href="http://www.wago.com/2009-114/000-023">www.wago.com/2009-114/000-023</a> |
| <b>Item no.: 2009-114/000-006</b><br>WMB-Inline; for Smart Printer; 2000 pieces on roll; stretchable 4 - 4.2 mm; plain; snap-on type; blue   | <a href="http://www.wago.com/2009-114/000-006">www.wago.com/2009-114/000-006</a> |
| <b>Item no.: 2009-114/000-024</b><br>WMB-Inline; for Smart Printer; 2000 pieces on roll; stretchable 4 - 4.2 mm; plain; snap-on type; violet | <a href="http://www.wago.com/2009-114/000-024">www.wago.com/2009-114/000-024</a> |
| <b>Item no.: 2009-114/000-012</b><br>WMB-Inline; for Smart Printer; 2000 pieces on roll; stretchable 4 - 4.2 mm; plain; snap-on type; orange | <a href="http://www.wago.com/2009-114/000-012">www.wago.com/2009-114/000-012</a> |
| <b>Item no.: 2009-114</b><br>WMB-Inline; for Smart Printer; 2000 pieces on roll; stretchable 4 - 4.2 mm; plain; snap-on type; white          | <a href="http://www.wago.com/2009-114">www.wago.com/2009-114</a>                 |
| <b>Item no.: 793-4501/000-002</b><br>WMB marking card; as card; stretchable 4 - 4.2 mm; plain; snap-on type; yellow                          | <a href="http://www.wago.com/793-4501/000-002">www.wago.com/793-4501/000-002</a> |
| <b>Item no.: 793-4501/000-006</b><br>WMB marking card; as card; stretchable 4 - 4.2 mm; plain; snap-on type; blue                            | <a href="http://www.wago.com/793-4501/000-006">www.wago.com/793-4501/000-006</a> |
| <b>Item no.: 793-4501</b><br>WMB marking card; as card; stretchable 4 - 4.2 mm; plain; snap-on type; white                                   | <a href="http://www.wago.com/793-4501">www.wago.com/793-4501</a>                 |
| <b>Item no.: 793-4501/000-023</b><br>WMB marking card; as card; stretchable 4 - 4.2 mm; plain; snap-on type; green                           | <a href="http://www.wago.com/793-4501/000-023">www.wago.com/793-4501/000-023</a> |
| <b>Item no.: 793-4501/000-024</b><br>WMB marking card; as card; stretchable 4 - 4.2 mm; plain; snap-on type; violet                          | <a href="http://www.wago.com/793-4501/000-024">www.wago.com/793-4501/000-024</a> |
| <b>Item no.: 793-4501/000-005</b><br>WMB marking card; as card; stretchable 4 - 4.2 mm; plain; snap-on type; red                             | <a href="http://www.wago.com/793-4501/000-005">www.wago.com/793-4501/000-005</a> |
| <b>Item no.: 793-4501/000-007</b><br>WMB marking card; as card; stretchable 4 - 4.2 mm; plain; snap-on type; gray                            | <a href="http://www.wago.com/793-4501/000-007">www.wago.com/793-4501/000-007</a> |

Subject to changes. Please also observe the further product documentation!





|  |  |
|--|--|
| <b>Item no.: 793-4501/000-012</b><br>WMB marking card; as card; stretchable 4 - 4.2 mm; plain; snap-on type; orange                                  | <a href="http://www.wago.com/793-4501/000-012">www.wago.com/793-4501/000-012</a> |
| <b>Item no.: 793-4501/000-017</b><br>WMB marking card; as card; stretchable 4 - 4.2 mm; plain; snap-on type; light green                             | <a href="http://www.wago.com/793-4501/000-017">www.wago.com/793-4501/000-017</a> |
| <b>Group marker carrier</b>  |  |
| <b>Item no.: 209-142</b><br>Group marker carrier; gray   | <a href="http://www.wago.com/209-142">www.wago.com/209-142</a>                   |
| <b>Item no.: 209-141</b><br>Group marker carrier; gray   | <a href="http://www.wago.com/209-141">www.wago.com/209-141</a>                   |
| <b>Item no.: 209-140</b><br>Group marker carrier; gray   | <a href="http://www.wago.com/209-140">www.wago.com/209-140</a>                   |
| <b>Item no.: 249-105</b><br>Group marker carrier; gray   | <a href="http://www.wago.com/249-105">www.wago.com/249-105</a>                   |
| <b>Carrier rail</b>  |  |
| <b>Mounting accessories</b>  |  |
| <b>Item no.: 210-197</b><br>Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; similar to EN 60715; silver-colored                     | <a href="http://www.wago.com/210-197">www.wago.com/210-197</a>                   |
| <b>Item no.: 210-198</b><br>Copper carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715; copper-colored                | <a href="http://www.wago.com/210-198">www.wago.com/210-198</a>                   |
| <b>Item no.: 210-504</b><br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; galvanized; according to EN 60715; silver-colored        | <a href="http://www.wago.com/210-504">www.wago.com/210-504</a>                   |
| <b>Item no.: 210-505</b><br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; galvanized; according to EN 60715; silver-colored      | <a href="http://www.wago.com/210-505">www.wago.com/210-505</a>                   |
| <b>Item no.: 210-506</b><br>Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; galvanized; similar to EN 60715; silver-colored       | <a href="http://www.wago.com/210-506">www.wago.com/210-506</a>                   |
| <b>Item no.: 210-508</b><br>Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; galvanized; similar to EN 60715; silver-colored         | <a href="http://www.wago.com/210-508">www.wago.com/210-508</a>                   |
| <b>Item no.: 210-113</b><br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; according to EN 60715; silver-colored                  | <a href="http://www.wago.com/210-113">www.wago.com/210-113</a>                   |
| <b>Item no.: 210-118</b><br>Steel carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715; silver-colored                 | <a href="http://www.wago.com/210-118">www.wago.com/210-118</a>                   |
| <b>Item no.: 210-112</b><br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 25 mm; silver-colored | <a href="http://www.wago.com/210-112">www.wago.com/210-112</a>                   |

Subject to changes. Please also observe the further product documentation!

**Item no.: 210-114**

Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; similar to EN 60715; silver-colored

[www.wago.com/210-114](http://www.wago.com/210-114)**Item no.: 210-115**Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 18 mm; silver-colored [www.wago.com/210-115](http://www.wago.com/210-115)**Item no.: 210-196**

Aluminum carrier rail; 35 x 8.2 mm; 1.6 mm thick; 2 m long; unslotted; similar to EN 60715; silver-colored

[www.wago.com/210-196](http://www.wago.com/210-196)**Jumpers**

## Jumper

**Item no.: 279-402**

Jumper; insulated; gray

[www.wago.com/279-402](http://www.wago.com/279-402)**Item no.: 279-409**

Jumper; insulated; gray

[www.wago.com/279-409](http://www.wago.com/279-409)**Item no.: 279-422**

Jumper; insulated; yellow-green

[www.wago.com/279-422](http://www.wago.com/279-422)**Item no.: 279-492**

Jumper; 2-way; insulated; gray

[www.wago.com/279-492](http://www.wago.com/279-492)**Item no.: 279-490**

Jumper; 10-way; insulated; gray

[www.wago.com/279-490](http://www.wago.com/279-490)**Item no.: 279-482**

Jumper; 2-way; insulated; gray

[www.wago.com/279-482](http://www.wago.com/279-482)**Item no.: 279-483**

Jumper; 3-way; insulated; gray

[www.wago.com/279-483](http://www.wago.com/279-483)**Downloads****Documentation****Bid Text**

|                        |              |                |          |
|------------------------|--------------|----------------|----------|
| 279-508<br>X81 - Datei | 2019 年2月19 日 | xml<br>3.4 kB  | Download |
| 279-508<br>doc - Datei | 2017 年2月28 日 | doc<br>25.1 kB | Download |

**Additional Information**

pdf  
2.3 MB  
Download

**CAD/CAE-Data**

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



#### CAD data

|                      |                     |                          |
|----------------------|---------------------|--------------------------|
| 2D/3D Models 279-508 | <a href="#">URL</a> | <a href="#">Download</a> |
|----------------------|---------------------|--------------------------|

#### CAE data

|                           |                     |                          |
|---------------------------|---------------------|--------------------------|
| EPLAN Data Portal 279-508 | <a href="#">URL</a> | <a href="#">Download</a> |
|---------------------------|---------------------|--------------------------|

|                        |                     |                          |
|------------------------|---------------------|--------------------------|
| WSCAD Universe 279-508 | <a href="#">URL</a> | <a href="#">Download</a> |
|------------------------|---------------------|--------------------------|

|                      |                     |                          |
|----------------------|---------------------|--------------------------|
| ZUKEN Portal 279-508 | <a href="#">URL</a> | <a href="#">Download</a> |
|----------------------|---------------------|--------------------------|

### Environmental Product Compliance

#### Compliance Search

|  |                     |                          |
|--|---------------------|--------------------------|
| Environmental Product Compliance 279-508 | <a href="#">URL</a> | <a href="#">Download</a> |
|--|---------------------|--------------------------|

Double-deck terminal block; 4-conductor through terminal block; L; suitable for Ex i applications; internal commoning; conductor entry with violet marking; for DIN-rail 35 x 15 and 35 x 7.5; 1.5 mm<sup>2</sup>; 1,50 mm<sup>2</sup>; gray

### Installation Notes



#### Double-deck marker carrier

(height including marker carrier)

Subject to changes. Please also observe the further product documentation!