


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00541	Connector, dc jack, 5.5x2.1x17.6 mm, molding style, spring contacts, nickel plated, 105° C	1	
2	56-00000	Hardware, nut, hex, 13x2.5 mm, M11x1.0, brass, nickel plated	1	
3	56-00001	Hardware, washer, lock, 14x11.1x1.1 mm, SPCC, nickel plated	1	
4	30-00795	Wire, 2C TS, 18 AWG, UL2651, 300V, 105C, 4.4 mm, VW-1, PVC, red and black	1	
5	24-00328	Overmold, panel mount jack, Nylon	1	Nylon UL 94 V-0, black



Installation Details
Panel thickness: 1.5 - 4.5
Recommended panel cutout:

Notes:
Functionally equivalent components may be substituted
Cables rated for 48 V, 7.5 A

Wiring Diagram	
50-00541	wire color
center	red
sleeve	black

Revision:	Date:	Description:	Prepared:	Notes:	<h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</p>				
A	3/27/2020	Initial release	AG <small>Digitally signed by AG Date: 2020.03.31 10:08:54 -07'00'</small>	RoHS compliant					
			Verified:	Function test: no open, no short circuit, no intermittent	<table border="1"> <tr> <td>Size:</td> <td>Part number:</td> </tr> <tr> <td>A</td> <td>10-03609</td> </tr> </table>	Size:	Part number:	A	10-03609
Size:	Part number:								
A	10-03609								
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Cable, 305 mm, 5.5x2.1 mm 50-00541 dc panel mount jack to stripped and tinned, 18 AWG, 30-00795	Scale: 1:1				

To see a custom version of this cable assembly, call Tensility at 541-323-3228 or email engineering@tensility.com