

Plug-in module - LDM- 48- 60DC - 2833699

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Plug-in module, for mounting on PR1 and PR2, with damping diode and yellow LED, polarity: A1-, A2+ (Japan standard), input voltage: 48 -60 V DC \pm 20%

Product Features

- Mechanical coding to protect against mismatching
- Attenuation of reverse voltage induced in coil



Key commercial data

| | |
|--------------------------------------|----------|
| Packing unit | 1 PCE |
| Minimum order quantity | 10 PCE |
| Weight per Piece (excluding packing) | 3.0 GRM |
| Custom tariff number | 85366990 |
| Country of origin | Italy |

Technical data

| | |
|---------------|---------------------|
| Product type | Plug-in module |
| Approval | UL Recognized |
| | cUL Recognized |
| | cULus Recognized |
| Design | PR1 |
| | PR2 |
| Input voltage | 48 V DC ... 60 V DC |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27371190 |
|------------|----------|

Plug-in module - LDM- 48- 60DC - 2833699

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.1 | 27371190 |
| eCl@ss 5.0 | 27371692 |
| eCl@ss 5.1 | 27371692 |
| eCl@ss 6.0 | 27371603 |
| eCl@ss 7.0 | 27371603 |
| eCl@ss 8.0 | 27371603 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001456 |
| ETIM 3.0 | EC001456 |
| ETIM 4.0 | EC001456 |
| ETIM 5.0 | EC001456 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211917 |
| UNSPSC 7.0901 | 39121516 |
| UNSPSC 11 | 39121516 |
| UNSPSC 12.01 | 39121516 |
| UNSPSC 13.2 | 39121516 |

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

| |
|---|
| UL Recognized  |
|---|

Plug-in module - LDM- 48- 60DC - 2833699

Approvals



Drawings

Plug-in module - LDM- 48- 60DC - 2833699

Circuit diagram

