



Figure similar

SIPLUS S7-1200 CPU 1215C DC/DC/relay based on 6ES7215-1HG40-0XB0 with conformal coating, -40...+70 °C, start up -25 °C, signal board: 0, compact CPU, DC/DC/relay, 2 PROFINET ports, onboard I/O: 14 DI 24 V DC 10 DQ relay 2 A, 2 AI 0-10 V DC 2 AQ 0-20 mA DC, power supply: DC 20.4-28.8 V DC, program/data memory 125 KB

| General information | |
|--|--|
| Product type designation | CPU 1215C DC/DC/relay |
| Firmware version | V4.1 |
| Engineering with | |
| <ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version | see entry ID: 109746275 |
| Supply voltage | |
| Rated value (DC) | |
| <ul style="list-style-type: none"> 24 V DC | Yes |
| permissible range, lower limit (DC) | 20.4 V |
| permissible range, upper limit (DC) | 28.8 V |
| Load voltage L+ | |
| <ul style="list-style-type: none"> Rated value (DC) permissible range, lower limit (DC) permissible range, upper limit (DC) | 24 V 5 V 250 V |
| Input current | |
| Current consumption (rated value) | 500 mA; CPU only |
| Current consumption, max. | 1 500 mA; CPU with all expansion modules |
| Inrush current, max. | 12 A; at 28.8 V DC |
| Encoder supply | |
| 24 V encoder supply | |
| <ul style="list-style-type: none"> 24 V | L+ minus 4 V DC min. |
| Power loss | |
| Power loss, typ. | 12 W |
| Memory | |
| Work memory | |
| <ul style="list-style-type: none"> integrated expandable | 100 kbyte No |
| Load memory | |
| <ul style="list-style-type: none"> integrated Plug-in (SIMATIC Memory Card), max. | 4 Mbyte with SIMATIC memory card |
| Backup | |
| <ul style="list-style-type: none"> present without battery | Yes; maintenance-free Yes |
| CPU processing times | |
| for bit operations, typ. | 0.085 µs; / instruction |
| for word operations, typ. | 1.7 µs; / instruction |
| for floating point arithmetic, typ. | 2.5 µs; / instruction |

| CPU-blocks | |
|---|---|
| Number of blocks (total) | DBs, FCs, FBs, counters and timers. The maximum number of addressable blocks ranges from 1 to 65535. There is no restriction, the entire working memory can be used |
| OB | |
| • Number, max. | Limited only by RAM for code |
| Data areas and their retentivity | |
| Retentive data area (incl. timers, counters, flags), max. | 10 kbyte |
| Flag | |
| • Size, max. | 8 kbyte; Size of bit memory address area |
| Address area | |
| Process image | |
| • Inputs, adjustable | 1 kbyte |
| • Outputs, adjustable | 1 kbyte |
| Hardware configuration | |
| Number of modules per system, max. | 3 communication modules, no signal board can be used, 8 signal modules |
| Time of day | |
| Clock | |
| • Hardware clock (real-time) | Yes |
| • Backup time | 480 h; Typical |
| • Deviation per day, max. | ±60 s/month at 25 °C |
| Digital inputs | |
| Number of digital inputs | 14; Integrated |
| • of which inputs usable for technological functions | 6; HSC (High Speed Counting) |
| Source/sink input | Yes |
| Number of simultaneously controllable inputs | |
| all mounting positions | |
| — up to 40 °C, max. | 14 |
| Input voltage | |
| • Rated value (DC) | 24 V |
| • for signal "0" | 5 V DC at 1 mA |
| • for signal "1" | 15 V DC at 2.5 mA |
| Input current | |
| • for signal "1", typ. | 1 mA |
| Input delay (for rated value of input voltage) | |
| for standard inputs | |
| — parameterizable | 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four |
| — at "0" to "1", min. | 0.2 ms |
| — at "0" to "1", max. | 12.8 ms |
| for interrupt inputs | |
| — parameterizable | Yes |
| for technological functions | |
| — parameterizable | Yes; Single phase : 3 at 100 kHz & 3 at 30 kHz, differential: 3 at 80 kHz & 3 at 30 kHz |
| Cable length | |
| • shielded, max. | 500 m; 50 m for technological functions |
| • unshielded, max. | 300 m; for technological functions: No |
| Digital outputs | |
| Number of digital outputs | 10; Relays |
| Switching capacity of the outputs | |
| • with resistive load, max. | 2 A |
| • on lamp load, max. | 30 W with DC, 200 W with AC |
| Output delay with resistive load | |
| • "0" to "1", max. | 10 ms; max. |
| • "1" to "0", max. | 10 ms; max. |
| Switching frequency | |
| • of the pulse outputs, with resistive load, max. | 1 Hz |
| Relay outputs | |

| | |
|--|--|
| <ul style="list-style-type: none"> Number of relay outputs Number of operating cycles, max. | 10 mechanically 10 million, at rated load voltage 100 000 |
| Cable length | |
| <ul style="list-style-type: none"> shielded, max. unshielded, max. | 500 m 150 m |
| Analog inputs | |
| Number of analog inputs | 2 |
| Input ranges | |
| <ul style="list-style-type: none"> Voltage | Yes |
| Input ranges (rated values), voltages | |
| <ul style="list-style-type: none"> 0 to +10 V — Input resistance (0 to 10 V) | Yes ≥100k ohms |
| Cable length | |
| <ul style="list-style-type: none"> shielded, max. | 100 m; twisted and shielded |
| Analog outputs | |
| Number of analog outputs | 2 |
| Output ranges, current | |
| <ul style="list-style-type: none"> 0 to 20 mA | Yes |
| Analog value generation for the inputs | |
| Integration and conversion time/resolution per channel | |
| <ul style="list-style-type: none"> Resolution with overrange (bit including sign), max. Integration time, parameterizable Conversion time (per channel) | 10 bit Yes 625 μs |
| Analog value generation for the outputs | |
| Integration and conversion time/resolution per channel | |
| <ul style="list-style-type: none"> Resolution with overrange (bit including sign), max. | 10 bit |
| Encoder | |
| Connectable encoders | |
| <ul style="list-style-type: none"> 2-wire sensor | Yes |
| 1. Interface | |
| Interface type | PROFINET |
| Isolated | Yes |
| automatic detection of transmission rate | Yes |
| Autonegotiation | Yes |
| Autocrossing | Yes |
| Interface types | |
| <ul style="list-style-type: none"> RJ 45 (Ethernet) | Yes |
| Protocols | |
| <ul style="list-style-type: none"> PROFINET IO Controller PROFINET IO Device | Yes Yes; Also simultaneously with IO-Device functionality |
| PROFINET IO Controller | |
| <ul style="list-style-type: none"> Transmission rate, max. | 100 Mbit/s |
| Services | |
| — Number of connectable IO Devices, max. | 16 |
| PROFINET IO Device | |
| Services | |
| — Shared device | Yes |
| — Number of IO Controllers with shared device, max. | 2 |
| Protocols | |
| Supports protocol for PROFINET IO | Yes |
| PROFIsafe | No |
| PROFIBUS | Yes; CM 1243-5 required |
| AS-Interface | Yes |
| Protocols (Ethernet) | |
| <ul style="list-style-type: none"> TCP/IP | Yes |
| Open IE communication | |
| <ul style="list-style-type: none"> TCP/IP ISO-on-TCP (RFC1006) | Yes Yes |

| | |
|--|--|
| • UDP | Yes |
| Web server | |
| • supported | Yes |
| • User-defined websites | Yes |
| Further protocols | |
| • MODBUS | Yes |
| communication functions / header | |
| S7 communication | |
| • supported | Yes |
| • as server | Yes |
| • as client | Yes |
| Number of connections | |
| • overall | 16; dynamically |
| Test commissioning functions | |
| Status/control | |
| • Status/control variable | Yes |
| • Variables | Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters |
| Forcing | |
| • Forcing | Yes |
| Diagnostic buffer | |
| • present | Yes |
| Traces | |
| • Number of configurable Traces | 2; Up to 512 KB of data per trace are possible |
| Integrated Functions | |
| Frequency measurement | Yes |
| controlled positioning | Yes |
| Number of position-controlled positioning axes, max. | 8 |
| PID controller | Yes |
| Number of alarm inputs | 4 |
| Potential separation | |
| Potential separation digital inputs | |
| • Potential separation digital inputs | 500V AC for 1 minute |
| • between the channels, in groups of | 1 |
| Potential separation digital outputs | |
| • Potential separation digital outputs | Relays |
| • between the channels | No |
| • between the channels, in groups of | 2 |
| EMC | |
| Interference immunity against discharge of static electricity | |
| • Interference immunity against discharge of static electricity acc. to IEC 61000-4-2 | Yes |
| — Test voltage at air discharge | 8 kV |
| — Test voltage at contact discharge | 6 kV |
| Interference immunity to cable-borne interference | |
| • Interference immunity on supply lines acc. to IEC 61000-4-4 | Yes |
| • Interference immunity on signal cables acc. to IEC 61000-4-4 | Yes |
| Interference immunity against voltage surge | |
| • Interference immunity on supply lines acc. to IEC 61000-4-5 | Yes |
| Interference immunity against conducted variable disturbance induced by high-frequency fields | |
| • Interference immunity against high-frequency radiation acc. to IEC 61000-4-6 | Yes |
| Emission of radio interference acc. to EN 55 011 | |
| • Limit class A, for use in industrial areas | Yes; Group 1 |
| • Limit class B, for use in residential areas | Yes; When appropriate measures are used to ensure compliance with the limits for Class B according to EN 55011 |
| Degree and class of protection | |
| IP degree of protection | IP20 |

Ambient conditions

| | |
|---|---|
| Free fall | |
| <ul style="list-style-type: none"> Fall height, max. | 0.3 m; five times, in product package |
| Ambient temperature during operation | |
| <ul style="list-style-type: none"> min. max. | -40 °C; = Tmin (incl. condensation/frost); start-up @ -25 °C 70 °C; = Tmax; Tmax > +55 °C number of simultaneously switched-on digital inputs 7, digital outputs 5, analog inputs 2, analog outputs 2 (no adjacent points) with horizontal mounting position; Tmax > +60 °C number of simultaneously switched-on digital inputs 7, digital outputs 5, analog inputs 1, analog outputs 1 (no adjacent points) with horizontal mounting position |
| <ul style="list-style-type: none"> At cold restart, min. | -25 °C |
| Ambient temperature during storage/transportation | |
| <ul style="list-style-type: none"> min. max. | -40 °C 70 °C |
| Altitude during operation relating to sea level | |
| <ul style="list-style-type: none"> Installation altitude above sea level, max. Ambient air temperature-barometric pressure-altitude | 2 000 m Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m); above 2 000 m max. 132 V AC |
| Relative humidity | |
| <ul style="list-style-type: none"> With condensation, tested in accordance with IEC 60068-2-38, max. | 100 %; RH incl. condensation/frost (no commissioning under condensation conditions) |
| Vibrations | |
| <ul style="list-style-type: none"> Vibration resistance during operation acc. to IEC 60068-2-6 Operation, tested according to IEC 60068-2-6 | 2 g (m/s ²) wall mounting, 1 g (m/s ²) DIN rail Yes |
| Shock testing | |
| <ul style="list-style-type: none"> tested according to IEC 60068-2-27 | Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms |
| Resistance | |
| Coolants and lubricants | |
| <ul style="list-style-type: none"> Resistant to commercially available coolants and lubricants | Yes; Incl. diesel and oil droplets in the air |
| Use in stationary industrial systems | |
| <ul style="list-style-type: none"> to biologically active substances according to EN 60721-3-3 to chemically active substances according to EN 60721-3-3 to mechanically active substances according to EN 60721-3-3 | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * Yes; Class 3S4 incl. sand, dust, * |
| Use on ships/at sea | |
| <ul style="list-style-type: none"> to biologically active substances according to EN 60721-3-6 to chemically active substances according to EN 60721-3-6 to mechanically active substances according to EN 60721-3-6 | Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * Yes; Class 6S3 incl. sand, dust; * |
| Usage in industrial process technology | |
| <ul style="list-style-type: none"> Against chemically active substances acc. to EN 60654-4 Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04 | Yes; Class 3 (excluding trichlorethylene) Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil) |
| Remark | |
| <ul style="list-style-type: none"> Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04 | * The supplied plug covers must remain in place over the unused interfaces during operation! |
| Conformal coating | |
| <ul style="list-style-type: none"> Coatings for printed circuit board assemblies acc. to EN 61086 Protection against fouling acc. to EN 60664-3 Military testing according to MIL-I-46058C, Amendment 7 Qualification and Performance of Electrical | Yes; Class 2 for high reliability Yes; Type 1 protection Yes; Discoloration of coating possible during service life Yes; Conformal coating, Class A |

Insulating Compound for Printed Board Assemblies
according to IPC-CC-830A

configuration / header

configuration / programming / header

Programming language

| | |
|-------|-----|
| — LAD | Yes |
| — FBD | Yes |
| — SCL | Yes |

programming / cycle time monitoring / header

| | |
|--------------|-----|
| • adjustable | Yes |
|--------------|-----|

Dimensions

| | |
|--------|--------|
| Width | 130 mm |
| Height | 100 mm |
| Depth | 75 mm |

Weights

| | |
|-----------------|-------|
| Weight, approx. | 585 g |
|-----------------|-------|

last modified: 4/1/2022 