

**FU1 thru FU5**Surface Mount Glass Passivated Superfast Rectifier
Reverse Voltage 50~600V Forward Current 1A

Features

- Glass passivated superfast recovery Rectifiers
- Very low profile - typical height of 1.0 mm
- Low forward voltage drop
- Low leakage current
- Moisture sensitivity: level 1, per J-STD-020
- AEC-Q101 qualified
- High temperature soldering guaranteed: 260 °C/10 seconds
- Halogen-free according to IEC 61249-2-21 definition

eSGA
(SOD-123FL)

Typical Applications

For use of general purpose rectification in lighting, cellular phone, portable device, power supplies and other consumer applications.

Maximum Ratings (TA = 25 °C unless otherwise noted)

Parameter	Symbol	FU1	FU2	FU3	FU4	FU5	Unit
Maximum repetitive peak reverse voltage	VRRM	50	100	200	400	600	V
Maximum RMS voltage	VRMS	35	70	140	280	420	V
Maximum DC blocking voltage	VDC	50	100	200	400	600	V
Maximum average forward rectified current	IF(AV)			1			A
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load	IFSM			30			A
Operating junction and storage temperature range	TJ, TSTG			- 55 to + 150			°C

Electrical Characteristics (TA = 25 °C unless otherwise noted)

Parameter	Test Conditions	Symbol	FU1	FU2	FU3	FU4	FU5	Unit
Maximum instantaneous forward voltage	1 A	V _F		0.95		1.3	1.7	Volts
Maximum DC reverse current at rated DC blocking voltage	TA=25°C TA=125°C	I _R			5.0 100			µA
Maximum reverse recovery time	I _F =0.5A, I _R =1.0A, I _{rr} =0.25A	t _{rr}			35			nS
Typical junction capacitance	4.0 V, 1 MHz	C _J		0.75				pF
Typical thermal resistance ¹⁾	junction to ambient	R _{θJA}		66				°C/W
	junction to case	R _{θJC}		32				
	junction to mount	R _{θJM}		1				

Note:1) The thermal resistance from junction to ambient,case or mount,mounted on P.C.B with 5×5mm copper pads,2 OZ,FR4 PCB

Ratings and Characteristics Curves

(TA = 25°C unless otherwise noted)




Figure 1. Forward Current Derating Curve




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current




Figure 3. Typical Reverse Characteristics




Figure 4. Typical Instantaneous Forward Characteristics








Figure 5. Typical Junction Capacitance


SURGE**FU1 thru FU5**Surface Mount Glass Passivated Superfast Rectifier
Reverse Voltage 50~600V Forward Current 1A

Package Outline Dimensions



DIM	Unit: mm		Unit: inch	
	MIN	MAX	MIN	MAX
A	0.9	1.08	0.035	0.043
A1	0	0.1	0.000	0.004
B	0.85	1.05	0.033	0.041
C	0.1	0.25	0.004	0.010
D	1.7	2	0.067	0.079
E	2.9	3.1	0.114	0.122
L	0.43	0.83	0.017	0.033
HE	3.5	3.9	0.138	0.154

Soldering footprint



Packing Information

Packing quantities:

3000 pcs/Reel, 40 Reels/Box; 8mm Tape, 7" Reel

Tape & Reel Specification

