


**7426**  
**54LS/74LS26**  
 QUAD 2-INPUT NAND BUFFER  
 (With Open-Collector Outputs)

**CONNECTION DIAGRAM**  
 PINOUT A

ORDERING CODE: See Section 9

PKGS	PIN OUT	COMMERCIAL GRADE	MILITARY GRADE	PKG TYPE
		$V_{CC} = +5.0 \text{ V} \pm 5\%$ , $T_A = 0^\circ \text{C to } +70^\circ \text{C}$	$V_{CC} = +5.0 \text{ V} \pm 10\%$ , $T_A = -55^\circ \text{C to } +125^\circ \text{C}$	
Plastic DIP (P)	A	7426PC, 74LS26PC		9A
Ceramic DIP (D)	A	7426DC, 74LS26DC	54LS26DM	6A
Flatpak (F)	A	7426FC, 74LS26FC	54LS26FM	3I



4

INPUT LOADING/FAN-OUT: See Section 3 for U.L. definitions

PINS	54/74 (U.L.) HIGH/LOW	54/74LS (U.L.) HIGH/LOW
Inputs	1.0/1.0	0.5/0.25
Outputs	OC**/10	OC**/5.0 (2.5)

DC AND AC CHARACTERISTICS: See Section 3\*

SYMBOL	PARAMETER	54/74		54/74LS		UNITS	CONDITIONS	
		Min	Max	Min	Max			
I <sub>OH</sub>	Output HIGH Current	50	50	1000	1000	$\mu\text{A}$	$V_{OH} = 12 \text{ V}$	$V_{CC} = \text{Min}$
							$V_{OH} = 15 \text{ V}$	$V_{IN} = V_{IL}$
I <sub>CCH</sub>	Power Supply Current	8.0	1.6	22	4.4	mA	$V_{IN} = \text{Gnd}$	$V_{CC} = \text{Max}$
							$V_{IN} = \text{Open}$	
t <sub>PLH</sub>	Propagation Delay	24	22	17	18	ns	Figs. 3-2, 3-4	
t <sub>PHL</sub>								

\*DC limits apply over operating temperature range; AC limits apply at  $T_A = +25^\circ \text{C}$  and  $V_{CC} = +5.0 \text{ V}$ .  
 \*\*OC—Open Collector